


Product Overview

The Microchip UPR5–UPR60e3 Powermite high efficiency rectifiers offer optimized forward voltage characteristics with reverse blocking capabilities from 50–600 volts. They are ideal for surface mount applications that operate at high frequencies.

In addition to its size advantages, Powermite package features include a full metallic bottom that eliminates possibility of solder flux entrapment during assembly and a unique locking tab acts as an efficient heat path from die to mounting plane for external heat sinking with very low thermal resistance junction to case (bottom). Its innovative design makes this device ideal for use with automatic insertion equipment. RoHS compliant versions are available.

Figure 1. DO-216AA Package



Features

- Low thermal resistance DO-216AA package for higher current operation
- Ultrafast recovery time of:
 - 25 ns for UPR5–UPR15e3
 - 50 ns for UPR20–UPR40e3
 - 30 ns for UPR60(e3)
- Efficient heat path with Integral locking bottom metal tab
- Low forward voltage
- Full metallic bottom eliminates flux entrapment
- Compatible with automatic insertion equipment
- Low profile-maximum height of 1.14 mm
- RoHS compliant versions available

Applications/Benefits

- Switching and regulating power supplies
- Charge pump circuits
- Reduces reverse recovery loss with low I_{RM}
- Small foot print (See [Mounting Pad Dimensions](#) details)

Table of Contents

Product Overview.....	1
1. Maximum Ratings.....	3
1.1. Mechanical Packaging.....	3
1.2. Part Nomenclature.....	3
2. Symbols and Definitions.....	4
2.1. Electrical Characteristics.....	4
3. Package Dimensions.....	5
3.1. Mounting Pad Dimensions.....	5
4. Revision History.....	6
Microchip Information.....	7
Trademarks.....	7
Legal Notice.....	7
Microchip Devices Code Protection Feature.....	7

1. Maximum Ratings

Table 1-1. Maximum Ratings

Parameters/Test Conditions	Symbol	Value	Unit
Junction and Storage Temperature	T_J and T_{STG}	–55 to +150	°C
Thermal Resistance Junction-to-Tab	—	30	°C/W
Thermal Resistance Junction-to-Bottom	—	10	°C/W
Non-Repetitive Peak Forward Surge Current (At 8.3 ms single half-sine wave)	I_{FSM}	UPR5–UPR15 25	A
		UPR20–UPR60 20	
Average Rectified Output Current ¹ (At rated V_{RWM} , $T_C = 75^\circ\text{C}$)	I_O	UPR5–UPR15 2.5	A
		UPR20–UPR60 2.0	
Solder Temperature at 10 seconds	—	260	°C

Note:


1. When mounted on FR-4 PC board using 1 oz copper with recommended minimum footprint.

1.1. Mechanical Packaging

- Case: Void-free transfer molded thermosetting epoxy compound meeting UL94V-0
- Terminals: Tin-lead or RoHS compliant annealed matte-tin plating. Solderable per MIL-STD-750, method 2026
- Marking: Date code, see electrical characteristics: device marking
- Polarity: Cathode designated by TAB 1
- Tape and Reel Option: 12 mm tape per standard EIA-481-B. Consult factory for quantities.
- Weight: Approximately 0.016 gram
- See [Package Dimensions](#)

1.2. Part Nomenclature

Figure 1-1. Part Nomenclature



2. Symbols and Definitions

Table 2-1. Symbols and Definitions

Symbol	Definition
I_F	Forward Current: The dc current flowing from the external circuit into the anode terminal.
I_{FSM}	Surge Peak Forward Current: The forward current including all nonrepetitive transient currents but excluding all repetitive transients (ref JESD282-B).
I_O	Average Rectified Output Current: The output current averaged over a full cycle with a 50 Hz or 60 Hz sine-wave input and a 180 degree conduction angle.
I_R	Reverse Current: The dc current flowing from the external circuit into the cathode terminal at the specified voltage V_R .
$I_{R(REC)}$	Reverse Recovery Current: The transient reverse current associated with a change from forward current to a reverse condition.
t_{rr}	Reverse Recovery Time: The time interval between the instant the current passes through zero when changing from the forward direction to the reverse direction and a specified decay point after a peak reverse current occurs.
V_F	Forward Voltage: A positive dc anode-cathode voltage the device will exhibit at a specified forward current.
V_R	Reverse Voltage: A positive dc cathode-anode voltage below the breakdown region.
V_{RWM}	Working Peak Reverse Voltage: The peak voltage excluding all transient voltages (ref JESD282-B). Also sometimes known historically as PIV.

2.1. Electrical Characteristics

Table 2-2. Electrical Characteristics at $T_A = +25\text{ }^{\circ}\text{C}$ Unless Otherwise Stated


Part Number	Device Marking ¹	Working Peak Reverse Voltage	Reverse Current	Reverse Current	Forward Current	Forward Voltage ³	Forward Voltage ³	Reverse Recovery Time
		V_{RWM}	I_R at V_{RWM}	I_R at V_{RWM} ($T_J = 100\text{ }^{\circ}\text{C}$)	I_F	V_F at I_F	V_F at I_F ($T_J = 100\text{ }^{\circ}\text{C}$)	t_{rr} at $I_F = 0.5\text{A}$ at $I_R = 1.0\text{A}$ at $I_{R(REC)} = 0.25\text{A}$
		V	μA	μA	A	V	V	ns
UPR5	R05	50	2	50	2	0.975	0.895	25
UPR10	R10	100	2	50	2	0.975	0.895	25
UPR15	R15	150	2	50	2	0.975	0.895	25
UPR20	R20	200	10	100	1	1.25	1.15	50
UPR30	R30	300	10	100	1	1.25	1.15	50
UPR40	R40	400	10	100	1	1.25	1.15	50
UPR60	R60	600	1	100 ⁽²⁾	2	1.6	1.4 ⁽⁴⁾	30

Notes:

1. Include • in marking for e3 parts (for example, UPR5e3 & R05•)
2. At $T_J = 125\text{ }^{\circ}\text{C}$
3. Short duration test pulse used to minimize self – heating effect.
4. At $T_J = 25\text{ }^{\circ}\text{C}$, $I_F = 1.2\text{A}$

3. Package Dimensions


Figure 3-1. Package Dimensions



Ltr	Dimensions			
	Inch		Millimeters	
	Min.	Max.	Min.	Max.
A	0.029	0.039	0.73	0.99
B	0.016	0.026	0.40	0.66
C	0.070	0.080	1.77	2.03
D	0.087	0.097	2.21	2.46
E	0.020	0.030	0.50	0.76
F	0.051	0.061	1.29	1.54
G	0.021	0.031	0.53	0.78
H	0.004	0.008	0.10	0.20
J	0.070	0.080	1.77	2.03
K	0.035	0.045	0.89	1.14

3.1. Mounting Pad Dimensions

Figure 3-2. Pad Layout



Ltr	Dimensions	
	Inch	Millimeters
A	0.100	2.54
B	0.105	2.67
C	0.050	1.27
D	0.030	0.76
E	0.025	0.64

4. Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

Revision	Date	Description
A	04/2025	Document was converted to Microchip template and assigned literature number DS00005917.
Rev. A	10/2024	Initial Microsemi document was created and assigned literature number RF01312.

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at <https://www.microchip.com/en-us/about/legal-information/microchip-trademarks>.

ISBN:

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip products are strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.