

Product Overview


The Microchip UPS1040–UPS10100e3 in Powermite 3 package, high efficiency rectifiers offer optimized forward voltage characteristics with reverse blocking capabilities from 40–100 volts. They are ideal for surface mount applications that operate at high frequencies. They offer high current/power capabilities previously only found in much larger packages.

In addition to its size advantages, Powermite 3 package features include a full metallic bottom that eliminates possibility of solder flux entrapment during assembly and a unique locking tab acts as an efficient heat path from die to mounting plane for external heat sinking with very low thermal resistance junction to case (bottom). Its innovative design makes this device ideal for use with automatic insertion equipment. RoHS compliant versions are available.

Features

- Low thermal resistance package for higher current operation
- Efficient heat path with Integral locking bottom metal tab
- High current capability with low forward voltage
- Guard-ring die construction for transient protection
- Full metallic bottom eliminates flux entrapment
- Compatible with automatic insertion equipment
- Low profile-maximum height of 1.14 mm
- RoHS compliant versions available

Figure 1. Powermite 3® Package



Applications

- Silicon Schottky (hot carrier) rectifier for minimal t_{rr} and minimal reverse recovery voltage
- Elimination of reverse-recovery oscillations to reduce need for EMI filtering.
- For use in high-frequency switching power supplies, inverters, free-wheeling diode applications, charge pump circuits, and polarity protection applications.
- Low forward power loss and high efficiency
- Reduces reverse recovery loss with low I_{RM}
- Robust package configuration for pick-and-place handling
- Full-metallic bottom eliminates flux entrapment
- Small foot print (See [Pad Layout](#) details)

Table of Contents

Product Overview..... 1

1. Maximum Ratings.....3

 1.1. Mechanical and Packaging.....3

 1.2. Part Nomenclature..... 3

2. Symbols and Definitions.....4

 2.1. Electrical Characteristics..... 4

3. Package Dimensions.....5

 3.1. Pad Layout..... 5

 3.2. Schematic.....5

4. Revision History..... 6

Microchip Information..... 7

 Trademarks..... 7

 Legal Notice.....7

 Microchip Devices Code Protection Feature.....7

1. Maximum Ratings

Table 1-1. Maximum Ratings at 25 °C Unless Otherwise Specified

Parameters/Test Conditions		Symbol	Value	Unit
Storage Temperature		T_{STG}	-55 to +150	°C
Junction Temperature		T_J	-55 to +125	°C
Working Peak Reverse Voltage	UPS1040	V_{RWM}	40	V
Peak Repetitive Reverse Voltage	UPS10100	V_{RRM}	100	
DC Blocking Voltage		V_R		
Thermal Resistance Junction-to-ambient		$R_{\theta JA}$	65	°C/W
Thermal Resistance Junction-to-case (bottom)	UPS1040	$R_{\theta JC}$	2.5	°C/W
	UPS10100		3.2	
Average Rectified Output Current ¹ (At rated V_{RWM})		I_O	5	A
Solder Temperature at 10 seconds		—	260	°C

Note:


- When mounted on FR-4 PC board using 2 oz copper with recommended minimum footprint.

1.1. Mechanical and Packaging

- Case: Void-free transfer molded thermosetting epoxy compound meeting UL94V-0
- Terminals: Tin-lead or RoHS compliant annealed matte-tin plating. Solderable per MIL-STD-750, method 2026
- Marking: MSC, See Electrical Characteristics: Device Marking, Date Code
- Polarity: Cathode designated by heatsink/Tab 3. See [Schematic](#)
- Tape and Reel Option: 16 mm tape per standard EIA-481-B. Consult factory for quantities.
- Weight: Approximately 0.072 gram
- See [Package Dimensions](#)

1.2. Part Nomenclature

Figure 1-1. Part Nomenclature



2. Symbols and Definitions

Table 2-1. Symbols and Definitions

Symbol	Definition
C_T	Total Capacitance: The total small signal capacitance between the diode terminals of a complete device.
I_F	Forward Current: The dc current flowing from the external circuit into the anode terminal
I_{FSM}	Surge Peak Forward Current: The forward current including all nonrepetitive transient currents but excluding all repetitive transients (ref JESD282-B)
I_O	Average Rectified Output Current: The Output Current averaged over a full cycle with a 50 Hz or 60 Hz sine-wave input and a 180 degree conduction angle.
I_R	Reverse Current: The dc current flowing from the external circuit into the cathode terminal at the specified voltage V_R
$V_{(BR)}$	Breakdown Voltage: A voltage in the breakdown region.
V_F	Forward Voltage: A positive dc anode-cathode voltage the device will exhibit at a specified forward current.
V_R	Reverse Voltage: A positive dc cathode-anode voltage below the breakdown region
$V_{R(RMS)}$	Reverse Voltage: Root-Mean-Square value of alternating component of a positive dc cathode-anode voltage
V_{RRM}	Repetitive Peak Reverse Voltage: The peak reverse voltage including all repetitive transient voltages but excluding all non-repetitive transient voltages.
V_{RWM}	Working Peak Reverse Voltage: The peak voltage excluding all transient voltages (ref JESD282-B). Also sometimes known historically as PIV.

2.1. Electrical Characteristics

Table 2-2. Electrical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$ Unless Otherwise Noted)


Part Number	Device Marking ⁽¹⁾	Working Peak Reverse Voltage	Max Reverse Current ⁽³⁾		RMS Reverse Voltage	Min Reverse Breakdown Voltage ⁽³⁾		Max Forward Voltage ⁽³⁾			Max Forward Voltage ⁽³⁾			Max Forward Surge Current ⁽⁵⁾	Capacitance at $V_R = 4\text{V}$ at $f = 1\text{ MHz}$
		V_{RWM}	I_R at V_{RWM}		$V_{R(RMS)}$	V_{BR} at I_{BR}	I_{BR}	I_F	V_F at I_F	V_F at $I_F^{(2)}$	I_F	V_F at I_F	V_F at $I_F^{(2)}$	I_{FSM}	C_T
		V	mA	mA ⁽²⁾	V	V	mA	A	V	V	A	V	V	A	pF
UPS1040	S1040	40	0.3	25 ⁽⁴⁾	28	40	1	8	0.49	0.41	10	0.51	—	150	700
UPS10100	S1010	100	0.3	20	70	100	0.5	5	0.64	0.62	10	0.75	0.72	150	—

Notes:

1. Include • in marking for e3 parts (for example, UPS1040e3 and S1040•)
2. At $T_j = 125\text{ }^{\circ}\text{C}$
3. Short duration test pulse used to minimize self-heating effect.
4. At $T_j = 100\text{ }^{\circ}\text{C}$
5. 8.3 ms single half sine wave superimposed on rated load

3. Package Dimensions


Figure 3-1. Package Dimensions



Dim.	Inch		Millimeters	
	Min.	Max.	Min.	Max.
A	0.068	0.072	1.73	1.83
B	0.172	0.174	4.37	4.43
C	0.197	0.204	5.01	5.17
D	0.035 NOM		0.889 NOM	
E	0.159	0.161	4.03	4.09
F	0.072 NOM		1.83 NOM	
G	0.056 NOM		1.422 NOM	
H	0.043	0.045	1.10	1.14
J	0.252	0.260	6.40	6.61
K	0.007 NOM		0.178 NOM	
L	0.028	0.030	0.71	0.77
M	0.014	0.018	0.36	0.46

3.1. Pad Layout


Figure 3-2. Pad Layout



Dim.	Inch	Millimeters
	Nominal	Nominal
A	0.190	4.826
B	0.210	5.344
C	0.038	0.965
D	0.034	0.864
E	0.030	0.762
F	0.030	0.762

3.2. Schematic

Figure 3-3. Schematic



4. Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

Revision	Date	Description
A	05/2025	Document was converted to Microchip template and assigned literature number DS00005970.
Rev. A	12/2024	Microsemi document was created and assigned literature number RF01317.

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at <https://www.microchip.com/en-us/about/legal-information/microchip-trademarks>.

ISBN: 979-8-3371-1211-4

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip products are strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.