

Microchip**Filter specification****TFS 614****1/5****Measurement condition**

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance:		
Input:	150	Ω
Output:	150	Ω

Characteristics

Remark:

The nominal frequency f_N is fixed at 614.0 MHz. The insertion loss a_e is defined as loss value determined at f_N . Reference level for the relative attenuation a_{rel} of the TFS 614 is the insertion loss a_e . All specified data are met within the operating temperature range.

D a t a		typ. value		tolerance / limit		
Insertion Loss (reference level)		a_e	2.2 dB	max.	4.5	dB
Nominal Frequency		f_N	-		614.4	MHz
Centre Frequency		f_C	614.4 MHz		-	
Bandwidth		BW				
3	dB		21.68 MHz		-	
Relative Attenuation		a_{rel}				
@	102.4 MHz		65 dB	min.	50	dB
@	204.8 MHz		70 dB	min.	50	dB
@	307.2 MHz		69 dB	min.	50	dB
@	409.6 MHz		68 dB	min.	50	dB
@	512.0 MHz		65 dB	min.	50	dB
@	716.8 MHz		64 dB	min.	50	dB
@	819.2 MHz		65 dB	min.	50	dB
@	921.6 MHz		60 dB	min.	50	dB
Input power level				max.	0	dBm
Operating Temperature Range		OTR	-		-40 °C ... +90 °C	
Storage Temperature Range			-		-45 °C ... +95 °C	
Temperature Coefficient of Frequency		TCf *	-77 ppm/K		-	



*) $\Delta f(\text{Hz}) = \text{TCf}(\text{ppm/K}) \times (T - T_0) \times f_{\text{CAT}}(\text{MHz})$. Material: LiNbO₃_64° black, so in principle pyrofree.

Generated:**Checked / Approved:**

Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30


Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Filter characteristic



Construction and pin connection


(All dimensions in mm)



1	Ground
2	Input
3	Ground
4	Ground
5	Ground
6	Output
7	Ground
8	Ground

Date code:	Year + week
E	2014
F	2015
G	2016
...	

150 Ω Test circuit



Microchip Frequency Technology GmbH

Potsdamer Straße 18

D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0.35 mm or g respectively, 1 octave per min, 10 cycles per plane, 3 planes; DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 15 min. each / 100 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;
for temperature conditions, see page 4: "Air reflow temperature conditions"
5. ESD ANSI/ESD S20.20-1999, class 1A for HBM

This filter is RoHS compliant (2011/65/EU)


Packing

Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;


max. pieces of filters per reel:	9000
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm

Tape (all dimensions in mm)

W	: 8,00 ± 0,3
Po	: 4,00 ± 0,1
Do	: 1,50 +0,1/-0
E	: 1,75 ± 0,1
F	: 3,50 ± 0,05
G(min)	: 0,75
P2	: 2,00 ± 0,05
P1	: 4,00 ± 0,1
D1(min)	: 1,50
Ao	: 3,25 ± 0,1
Bo	: 3,25 ± 0,1
Ct	: 5,5 ± 0,1

**Reel (all dimensions in mm)**

A	: 330
W1	: 8,4 +1,5/-0
W2(max)	: 14,4
N(min)	: 50
C	: 13,0 +0,5/-0,2



The minimum bending radius is 45 mm.

Microchip Frequency Technology GmbH

Potsdamer Straße 18


D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	Exposure
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile**Microchip Frequency Technology GmbH****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Microchip**Filter specification****TFS 614****5/5****History**

Version	Reason of Changes	Name	Date
1.0	Generation of development specification	Strehl	30.10.2008
1.1	Add typical values, add filter characteristic Generation of filter specification	S. Channaa	24.02.2009
2.0	Changed pull off direction from reel	Schönbein	29.05.2012
2.1	Remark on pyrofree material added to data table	Schönbein	25.04.2013
2.2	Maximum input power updated	Kortenbeutel	16.01.2014