Measurement condition

Ambient temperature T_A:	23	°C
Input power level:	0	dBm
Terminating impedance:		
Input:	50	Ω
Output:	50	Ω

Characteristics

Remark:
The maximum attenuation in the passband is defined as the insertion loss a_e. The nominal frequency f_N is fixed at 704 MHz without any tolerance or limit. The values of absolute attenuation a_{abs} are guaranteed for the whole operating temperature range. The frequency shift of the filter in the operating temperature range is included in the production tolerance scheme.

D a t a			**typ. value**		**tolerance / limit**		
Insertion loss	a_e		1.8	dB	max.	3.0	dB
Nominal frequency	f_N		-			704.0	MHz
Passband	PB		-		f_N ±	12.0	MHz
Passband variation			0.5	dB	max.	1.0	dB
Absolute attenuation	a_{abs}						
1 MHz … 200 MHz			57	dB	min.	50.0	dB
200 MHz … 555 MHz			60	dB	min.	55.0	dB
555 MHz … 624 MHz			55	dB	min.	33.5	dB
784 MHz … 853 MHz			45	dB	min.	33.5	dB
853 MHz … 1004 MHz			46	dB	min.	42.0	dB
Group delay ripple within PB	p-p		14	ns	max.	200	ns
Input power level			-		max.	10	dBm
Operating temperature range	OTR		-		-10 °C ... +75 °C		
Storage temperature range			-		-55 °C ... +125 °C		
Temperature coefficient of frequency	TC_f	*)	-76	ppm/K			

*) $\Delta f = TC_f(T - T_A)f_N$


Generated:


Checked / Approved:

Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.


Filter characteristic





Construction and pin connection


(All dimensions in mm)



1	Ground
2	Input
3	Ground
4	Ground
5	Ground
6	Output
7	Ground
8	Ground

Date code:	Year + week
K	2018
L	2019
M	2020
...	

50 Ω Test circuit



Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Stability characteristics, reliability

After the following tests the filter shall meet the whole specification:

1. Shock: 500 g, 1 ms, half sine wave, 3 shocks each plane;
   DIN IEC 60068 T2 - 27

2. Vibration: 10 Hz to 2000 Hz, 0.35 mm or 5 g respectively, 1 octave per min, 10 cycles per plane, 3 planes; DIN IEC 60068 T2 - 6

3. Change of temperature: -55 °C to 125 °C / 15 min. each / 100 cycles
   DIN IEC 60068 part 2 – 14 Test N

4. Resistance to solder heat (reflow): reflow possible: three times max.;
   for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;


5. SAW devices are Electrostatic Discharge (ESD) sensitive devices.

This filter is RoHS compliant (2011/65/EU)

Packing


Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;

reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm



Tape (all dimensions in mm)

W	:	12.00	±0.3
Po	:	4.00	±0.1
Do	:	1.50	+0.1/-0
E	:	1.75	±0.1
F	:	5.50	±0.05
G(min)	:	0.75	
P2	:	2.00	±0.05
P1	:	8.00	±0.1
D1(min)	:	1.50	
Ao	:	4.30	±0.1
Bo	:	4.30	±0.1
Ct	:	9.2	±0.1
Ko	:	1.80	±0.1
t	:	0.30	±0.05



Reel (all dimensions in mm)

A	:	330	or 180
W1	:	12.4	+2/-0
W2(max)	:	18.40	
N(min)	:	50.00	
C	:	13.0	+0.5/-0.2

The minimum bending radius is 45 mm.


Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

Conditions	**Exposure**
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

Chip-mount air reflow profile



Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

History

Version	Reason of Changes	Name	Date
1.0	- Generation of development specification	Strehl	16.03.2008
2.0	- Change attenuation, add typical values and filter characteristic - Generation of filter specification	Channaa	27.08.2009
2.1	- Maximum input power updated	Kortenbeutel	07.01.2014
3.0	- Intermodulation limits removed - Maximum input power corrected - Typos corrected - Update of package drawing - Orientation of tape and reel updated	Molke	03.07.2018

Microchip Frequency Technology GmbH
Potsdamer Straße 18
D 14 513 TELTOW / Germany
Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.