

Microchip**Filter Specification****TFS 246 H4****1/5****Measurement condition**

Ambient temperature: 23 °C
 Input power level: 0 dBm
 Terminating impedances *)
 Input: 490 Ω || -2.62 pF
 Output: 490 Ω || -2.62 pF
 External coil: 270 nH

Characteristics**Remark:**

Reference level for the relative attenuation a_{rel} of the TFS246H4 is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The centre frequency f_c is the arithmetic mean value of the upper and lower frequencies at the 3 dB filter attenuation level relative to the insertion loss a_e . The nominal frequency f_N is fixed at 246 MHz without any tolerance. The given values for the relative attenuation a_{rel} and for the group delay ripple have to be reached at the frequencies given below even if the centre frequency f_c is shifted due to the temperature coefficient of frequency TC_f in the operating temperature range and due to a production tolerance for the centre frequency f_c .

D a t a		typ. value		tolerance / limit		
Insertion loss (Reference level)	$a_e = a_{min}$	2,5	dB	max	5	dB
Nominal frequency	f_N	-			246,000	MHz
Pass band ripple $f_N - 85$ kHz ... $f_N + 93$ kHz		0,5	dB	max	1,5	dB
Relative attenuation	a_{rel}					
f_N	$f_N \pm 120$ kHz	1,5	dB	max	3	dB
$f_N \pm 330$ kHz ... $f_N \pm 400$ kHz		22	dB	min	18	dB
$f_N \pm 400$ kHz ... $f_N \pm 600$ kHz		33	dB	min	25	dB
$f_N \pm 600$ kHz ... $f_N \pm 800$ MHz		41	dB	min	40	dB
$f_N \pm 800$ kHz ... $f_N \pm 1,6$ MHz		47...55	dB	min	45	dB
$f_N \pm 1,6$ MHz ... $f_N \pm 3,0$ MHz		52...55	dB	min	45	dB
$f_N \pm 3,0$ MHz ... $f_N \pm 20$ MHz		54	dB	min	46	dB
$f_N \pm 20$ MHz ... $f_N \pm 100$ MHz		55...70	dB	min	45	dB
Group delay distortion	GDD					
$f_N \pm 50$ kHz		0,5	µs	max	1,2	µs
$f_N \pm 70$ kHz		0,8	µs	max	1,5	µs
$f_N \pm 100$ kHz		1,2	µs	max	2,5	µs
Operating temperature range		-		- 25 °C ... + 85 °C		
Storage temperature range		-		- 30 °C ... + 85 °C		
Temperature coefficient of frequency TC_f **)		- 0,036	ppm/K ²	-		
Frequency inversion temperature T_0		+ 25	°C	-		

*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

**) $\Delta f(\text{Hz}) = TC_f(\text{ppm/K}^2) \times (T - T_0)^2 \times f_{T0}(\text{MHz})$

Generated:**Checked / approved:**

Microchip Frequency Technology GmbH

Potsdamer Straße 18


D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.



Microchip**Filter Specification****TFS 246 H4****2/5****Construction and pin configuration**

(All dimensions in mm)



Datecode	Year + week
M	2000
N	2001
P	2002
...	

1	Input
7	Output
3,4	External coil
2,5,6,8,9,10,11,12	Ground

50 Ohm Test circuit 1**50 Ohm Test circuit 2****Microchip Frequency Technology GmbH****Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Microchip**Filter Specification****TFS 246 H4****3/5****Stability characteristics**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;

Packing

Tape & Reel: IEC 286 - 3, with exception of value for N and minimum bending radius;
tape type II, embossed carrier tape with top cover tape on the upper side;

max. pieces of filters per reel:

Reel of empty components at start:


Reel of empty components at start including leader:

Trailer


3000
min 300 mm
min 500 mm
min 300 mm

Tape (all dimensions in mm)

W	: 16 ± 0,3
Po	: 4 ± 0,1
Do	: 1,5 ± 0,1
E	: 1,75 ± 0,1
F	: 7,5 ± 0,1
G (min)	: 0,6
P2	: 2 ± 0,1
P1	: 8 ± 0,1
D1(min)	: 1,5
Ao	: 5,5 ± 0,1
Bo	: 7,5 ± 0,1

**Reel (all dimensions in mm):**

A	: 330
W1	: 16,4 +2
W2 (max)	: 22,4
N (min)	: 50
C	: 13 + 0,5 / - 0,2



The minimum bending radius is 45 mm. The mounting surface of the filters faces the bottom side of the embossed carrier tape. Markings on the filters can be read if the upper side of the carrier tape is regarded with the sprocket holes on its right.

Microchip Frequency Technology GmbH

Potsdamer Straße 18

D 14 513 TELTOW / Germany

Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Air reflow temperature conditions

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	


Chip-mount air reflow profile

Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

Microchip Frequency Technology GmbH**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Microchip**Filter Specification****TFS 246 H4****5/5****History**

Version	Reason of Changes	Name	Date
1.0	Generate specification according to customer's requirements	Dr. Wall	07.02.2002
1.1	Add and correct typical data. Correct value for coupling coil.	Dr. Wall	27.03.2002
1.2	Change operating temperature range from –20°C ... 85°C to –25°C ... 85°C	Dr. Wall	19.04.2002
1.3	Correct typo for first selection value (from 8 to 18 dB)	Dr. Wall	16.05.2002

Microchip Frequency Technology GmbH**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**

Microchip Frequency Technology GmbH reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.