APT5010B2FLL
APT5010LFLL
500V 46A 0.100Ω

POWER MOS 7® FREDFET



Power MOS 7® is a new generation of low loss, high voltage, N-Channel enhancement mode power MOSFETS. Both conduction and switching losses are addressed with Power MOS 7® by significantly lowering $R_{DS(ON)}$ and Q_g. Power MOS 7® combines lower conduction and switching losses along with exceptionally fast switching speeds inherent with APT's patented metal gate structure.

- **Lower Input Capacitance**
- **Lower Miller Capacitance**
- **Lower Gate Charge, Qg**
- **Increased Power Dissipation**
- **Easier To Drive**
- **Popular T-MAX™ or TO-264 Package**
- **FAST RECOVERY BODY DIODE**



MAXIMUM RATINGS All Ratings: T_C = 25°C unless otherwise specified.

Symbol	Parameter	APT5010B2FLL_LFLL	UNIT
V_{DSS}	Drain-Source Voltage	500	Volts
I_D	Continuous Drain Current @ T_C = 25°C	46	Amps
I_{DM}	Pulsed Drain Current ①	184	
V_{GS}	Gate-Source Voltage Continuous	±30	Volts
V_{GSM}	Gate-Source Voltage Transient	±40	
P_D	Total Power Dissipation @ T_C = 25°C	520	Watts
	Linear Derating Factor	4.0	W/°C
T_J,T_{STG}	Operating and Storage Junction Temperature Range	-55 to 150	°C
T_L	Lead Temperature: 0.063" from Case for 10 Sec.	300	
I_{AR}	Avalanche Current ① (Repetitive and Non-Repetitive)	50	Amps
E_{AR}	Repetitive Avalanche Energy ①	50	mJ
E_{AS}	Single Pulse Avalanche Energy ④	1600	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Characteristic / Test Conditions	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage (V_{GS} = 0V, I_D = 250μA)	500			Volts
$R_{DS(on)}$	Drain-Source On-State Resistance ② (V_{GS} = 10V, I_D = 23A)			0.100	Ohms
I_{DSS}	Zero Gate Voltage Drain Current (V_{DS} = 500V, V_{GS} = 0V)			250	μA
	Zero Gate Voltage Drain Current (V_{DS} = 400V, V_{GS} = 0V, T_C = 125°C)			1000	
I_{GSS}	Gate-Source Leakage Current (V_{GS} = ±30V, V_{DS} = 0V)			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage (V_{DS} = V_{GS}, I_D = 2.5mA)	3		5	Volts

CAUTION: These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

APT Website - http://www.advancedpower.com

050-7028 Rev D 9-2004

DYNAMIC CHARACTERISTICS

Symbol	Characteristic	Test Conditions	MIN	TYP	MAX	UNIT
C_{iss}	Input Capacitance	V_{GS} = 0V V_{DS} = 25V f = 1 MHz		4360		pF
C_{oss}	Output Capacitance			895		
C_{rss}	Reverse Transfer Capacitance			60		
Q_g	Total Gate Charge ③	V_{GS} = 10V V_{DD} = 250V I_D = 46A @ 25°C		95		nC
Q_{gs}	Gate-Source Charge			24		
Q_{gd}	Gate-Drain ("Miller") Charge			50		
$t_{d(on)}$	Turn-on Delay Time	**RESISTIVE SWITCHING** V_{GS} = 15V V_{DD} = 250V I_D = 46A@ 25°C R_G = 0.6Ω		11		ns
t_r	Rise Time			15		
$t_{d(off)}$	Turn-off Delay Time			25		
t_f	Fall Time			3		
E_{on}	Turn-on Switching Energy ⑥	**INDUCTIVE SWITCHING @ 25°C** V_{DD} = 333V, V_{GS} = 15V I_D = 46A, R_G = 5Ω		545		µJ
E_{off}	Turn-off Switching Energy			510		
E_{on}	Turn-on Switching Energy ⑥	**INDUCTIVE SWITCHING @ 125°C** V_{DD} = 333V V_{GS} = 15V I_D = 46A, R_G = 5Ω		845		
E_{off}	Turn-off Switching Energy			595		

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Symbol	Characteristic / Test Conditions		MIN	TYP	MAX	UNIT
I_S	Continuous Source Current (Body Diode)				46	Amps
I_{SM}	Pulsed Source Current ① (Body Diode)				184	
V_{SD}	Diode Forward Voltage ② (V_{GS} = 0V, I_S = -46A)				1.3	Volts
$^{dv}/_{dt}$	Peak Diode Recovery $^{dv}/_{dt}$ ⑤				15	V/ns
t_{rr}	Reverse Recovery Time (I_S = -46A, $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C			280	ns
		T_j = 125°C			600	
Q_{rr}	Reverse Recovery Charge (I_S = -46A, $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C		2.28		µC
		T_j = 125°C		6.41		
I_{RRM}	Peak Recovery Current (I_S = -46A, $^{di}/_{dt}$ = 100A/µs)	T_j = 25°C		15.7		Amps
		T_j = 125°C		23.6		

THERMAL CHARACTERISTICS

Symbol	Characteristic	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction to Case			0.25	°C/W
$R_{\theta JA}$	Junction to Ambient			40	

① Repetitive Rating: Pulse width limited by maximum junction temperature
② Pulse Test: Pulse width < 380 µs, Duty Cycle < 2%
③ See MIL-STD-750 Method 3471
④ Starting T_j = +25°C, L = 1.51mH, R_G = 25Ω, Peak I_L = 46A
⑤ $^{dv}/_{dt}$ numbers reflect the limitations of the test circuit rather than the device itself. $I_S \le -I_D$46A $^{di}/_{dt} \le$ 700A/µs $V_R \le$ 500V $T_J \le$ 150°C
⑥ Eon includes diode reverse recovery. See figures 18, 20.

APT Reserves the right to change, without notice, the specifications and inforation contained herein.



FIGURE 1, MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION



FIGURE 2, TRANSIENT THERMAL IMPEDANCE MODEL



FIGURE 3, LOW VOLTAGE OUTPUT CHARACTERISTICS



FIGURE 4, TRANSFER CHARACTERISTICS



FIGURE 5, R_{DS}(ON) vs DRAIN CURRENT



FIGURE 6, MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE



FIGURE 7, BREAKDOWN VOLTAGE vs TEMPERATURE



FIGURE 8, ON-RESISTANCE vs. TEMPERATURE



FIGURE 9, THRESHOLD VOLTAGE vs TEMPERATURE



FIGURE 10, MAXIMUM SAFE OPERATING AREA



FIGURE 11, CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE



FIGURE 12, GATE CHARGES vs GATE-TO-SOURCE VOLTAGE



FIGURE 13, SOURCE-DRAIN DIODE FORWARD VOLTAGE



FIGURE 14, DELAY TIMES vs CURRENT



FIGURE 15, RISE AND FALL TIMES vs CURRENT



FIGURE 16, SWITCHING ENERGY vs CURRENT



FIGURE 17, SWITCHING ENERGY VS. GATE RESISTANCE



Figure 18, Turn-on Switching Waveforms and Definitions



Figure 19, Turn-off Switching Waveforms and Definitions



Figure 20, Inductive Switching Test Circuit

T-MAX™ (B2) Package Outline



These dimensions are equal to the TO-247 without the mounting hole.

Dimensions in Millimeters and (Inches)

TO-264 (L) Package Outline



Dimensions in Millimeters and (Inches)

APT's products are covered by one or more of U.S.patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. US and Foreign patents pending. All Rights Reserved.