

5 Amp Ultra Low Forward Voltage Schottky Rectifier

LSM535J-LSM545JE3
LSM535G-LSM545GE3



Product Overview

The LSM5xx series provides a 5 Amp, Schottky surface mount rectifier with low forward voltage and low leakage current. The SMCJ J-bend design in the DO-214AB package allows for greater PC board mounting density. The SMCG Gull-wing design in the DO-215AB package is ideal for visible solder connections. For critical applications requiring very fast switching, these very low forward voltage Schottkys with their "hot carrier" features provide extremely fast switching to replace conventional ultrafast rectifiers.

Features

- Schottky Barrier Rectifier
- Surface Mount Plastic Package
- Guard Ring for Reverse Protection
- High Surge Capability
- Ultra Low Forward Voltage
- Schottky OR'ing diode
- RoHS compliant versions are available with an e3 suffix
- Moisture classification is a level 1 with no dry pack required per IPC/JEDEC J-STD-020F

Figure 1. DO-215AB (SMCG) Package




Figure 2. DO-214AB (SMCJ) Package



Applications/Benefits

- Silicon Schottky (hot carrier) rectifier for minimal t_{rr} and elimination of reverse-recovery oscillations to reduce need for EMI filtering
- For use in high-frequency switching power supplies, inverters, freewheeling, polarity protection, or "OR'ing" applications
- Low forward power loss and high efficiency

Note: All SMC series are equivalent to prior SMM package identifications.

Table of Contents

Product Overview..... 1

 Features.....1

 Applications/Benefits..... 1

1. Maximum Ratings.....3

 1.1. Mechanical and Packaging.....3

2. Part Nomenclature.....4

 2.1. Symbols and Definitions..... 4

3. Electrical Characteristics.....5

4. Package Dimensions..... 6

5. Pad Layout.....7

6. Revision History..... 8

Microchip Information..... 9

 Trademarks..... 9

 Legal Notice.....9

 Microchip Devices Code Protection Feature.....9

1. Maximum Ratings

Table 1-1. Maximum Ratings at 25 °C Unless Otherwise Noted

Parameters/Test Conditions	Symbol	Value	Unit
Storage Temperature	T_{STG}	-55 to +150	°C
Junction Temperature	T_J	-55 to +150	°C
Thermal Resistance Junction-to-Lead	$R_{\theta JL}$	22	°C/W
Forward Surge Current ¹	I_{FSM}	250	A
Average Rectified Forward Current (Square Wave)	I_O	5.0	A
Solder Temperature at 10 s	—	260	°C

Note:


- At 8.3 ms single half-sine waveform superimposed on rated load (JEDEC method), $T_J = 150\text{ °C}$.

1.1. Mechanical and Packaging

- Case: Void-free transfer molded thermosetting epoxy body meeting UL94V-0
- Terminals: Tin-lead or RoHS compliant annealed matte-tin plating, readily solderable per MIL-STD-750, method 2026
- Polarity: Indicated by cathode band
- Tape-and-Reel: Standard per EIA-481-B (add "TR" suffix to part number). Consult factory for quantities.
- Weight: Approximately 0.13 grams
- See [Package Dimensions](#)

2. Part Nomenclature

Figure 2-1. Part Nomenclature



2.1. Symbols and Definitions

Table 2-1. Symbols and Definitions

Symbol	Definition
C_j	Junction Capacitance: The total small signal capacitance between the diode terminals of a complete device.
I_F	Forward Current: The forward current dc value, no alternating component.
I_{FSM}	Maximum Forward Surge Current: The forward current, surge peak or rated forward surge current.
I_O	Average Rectified Forward Current: The current average over a full cycle with a 180 degree conduction angle (square wave).
I_R	Reverse Current: The maximum reverse (leakage) current that will flow at the specified voltage and temperature.
V_F	Maximum Forward Voltage: The maximum forward voltage the device will exhibit at a specified current.
V_R	Reverse Voltage: The reverse voltage dc value, no alternating component.
V_{RRM}	Repetitive Peak Reverse Voltage: The peak reverse voltage including all repetitive transient voltages but excluding all non-repetitive transient voltages.
V_{RWM}	Working Peak Reverse Voltage: The maximum peak voltage that can be applied over the operating temperature range excluding all transient voltages (ref JESD282-B). Also sometimes known as PIV.

3. Electrical Characteristics

Table 3-1. Electrical Characteristics at 25 °C Unless Otherwise Stated


Part Number	Device Marking	Working Peak Reverse Voltage V_{RWM} Volts	Reverse Current I_R $T_J = 25\text{ }^{\circ}\text{C}$ at V_{RWM} mA	Reverse Current I_R $T_J = 125\text{ }^{\circ}\text{C}$ at V_{RWM} mA	Peak Forward Voltage ¹ V_F at 5A $T_J = 25\text{ }^{\circ}\text{C}$ V_{FM} Volts	Peak Forward Voltage ¹ V_F at 5A $T_J = 150\text{ }^{\circ}\text{C}$ V_{FM} Volts	Junction Capacitance at 5V C_J pF
		MAX	MAX	MAX	MAX	MAX	Typical
LSM535(G/J)(e3)	L535	35	2	500	0.52	0.42	380
LSM540(G/J)(e3)	L540	40	2	500	0.52	0.42	380
LSM545(G/J)(e3)	L545	45	2	500	0.52	0.42	380

Note:

1. Obtained through square wave pulse with a pulse width of 300 μs and a 2% duty cycle.


4. Package Dimensions

Figure 4-1. SMCG (DO-215AB)



Ltr	Dimensions			
	Inch		Millimeters	
	Min	Max	Min	Max
A	0.117	0.123	2.97	3.12
B	0.260	0.280	6.60	7.11
C	0.220	0.245	5.59	6.22
E	0.075	0.095	1.91	2.41
F	0.380	0.400	9.65	10.16
K	0.025	0.040	0.640	1.02

Figure 4-2. SMCJ (DO-214AB)



Ltr	Dimensions			
	Inch		Millimeter	
	Min	Max	Min	Max
A	0.117	0.123	2.97	3.12
B	0.260	0.280	6.60	7.11
C	0.220	0.245	5.59	6.22
D	0.307	0.322	7.80	8.18
E	0.075	0.095	1.91	2.41
L	0.030	0.060	0.760	1.52

5. Pad Layout

Figure 5-1. Pad Layout




Table 5-1. SMCG (DO-215AB)

Ltr	Inch	Millimeters
A	0.510	12.95
B	0.110	2.79
C	0.150	3.81

Table 5-2. SMCJ (DO-214AB)

Ltr	Inch	Millimeter
A	0.390	9.90
B	0.110	2.79
C	0.150	3.81

6. Revision History

Revision	Date	Description
A	08/2025	Initial version

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at <https://www.microchip.com/en-us/about/legal-information/microchip-trademarks>.

ISBN: 979-8-3371-1767-6

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip products are strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.