


1700V, 750 mΩ N-Channel mSiC™ MOSFET

MSC750SMA170SD



Product Overview

1700V, 750 mΩ typical at $V_{GS} = 20V$, 871 mΩ typical at $V_{GS} = 18V$, Silicon Carbide (SiC) N-Channel MOSFET, TO-263 7-lead XL with a source sense.



Features

- Low capacitances and low gate charge
- Fast switching speed due to low internal gate resistance (ESR)
- Stable operation at high junction temperature, $T_{J(max)} = 175\text{ }^{\circ}\text{C}$
- Fast and reliable body diode
- Superior avalanche ruggedness
- RoHS compliant

Benefits

- High efficiency to enable lighter and more compact system
- Simple to drive and easy to parallel
- Improved thermal capabilities and lower switching losses
- Eliminates the need for external freewheeling diode
- Lower system cost of ownership

Applications

- Photovoltaic (PV) inverter, converter, and industrial motor drives
- Smart grid transmission and distribution
- Induction heating and welding
- Hybrid Electric Vehicle (HEV) powertrain and Electric Vehicle (EV) charger
- Power supply and distribution

1. Device Specifications

This section shows the specifications of this device.

1.1 Absolute Maximum Ratings

The following table shows the absolute maximum ratings of this device.

Table 1-1. Absolute Maximum Ratings

Symbol	Parameter	Ratings	Unit
V_{DSS}	Drain source voltage	1700	V
I_D	Continuous drain current at $T_C = 25\text{ }^\circ\text{C}$	6.0	A
	Continuous drain current at $T_C = 100\text{ }^\circ\text{C}$	5.0	
I_{DM}	Pulsed drain current ¹	14	
V_{GS}	Gate-source voltage	23 to -10	V
	Transient gate-source voltage	25 to -12	
P_D	Total power dissipation at $T_C = 25\text{ }^\circ\text{C}$	74	W
	Linear derating factor	0.49	

Note:

1. Repetitive rating; pulse width and case temperature are limited by the maximum junction temperature.

The following table shows the thermal and mechanical characteristics of this device.

Table 1-2. Thermal and Mechanical Characteristics

Symbol	Characteristic/Test Conditions	Min.	Typ.	Max.	Unit
$R_{\theta JC}$	Junction-to-case thermal resistance	—	1.57	2.03	$^\circ\text{C/W}$
T_J	Operating junction temperature	-55	—	175	$^\circ\text{C}$
T_{STG}	Storage temperature	-55	—	150	
—	Reflow temperature	—	—	260	$^\circ\text{C}$
Wt	Package weight	—	1.6	—	g

ESD practices should comply with JESD-625.

1.2 Electrical Performance

The following table shows the static characteristics of this device. $T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified.

Table 1-3. Static Characteristics

Symbol	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0V, I_D = 100\text{ }\mu\text{A}$	1700	—	—	V
$R_{DS(on)}$	Drain-source on resistance ¹	$V_{GS} = 20V, I_D = 2.5A$	—	750	940	$\text{m}\Omega$
		$V_{GS} = 18V, I_D = 2.5A$	—	871	—	
$V_{GS(th)}$	Gate-source threshold voltage	$V_{GS} = V_{DS}, I_D = 100\text{ }\mu\text{A}$	1.9	3.0	5.0	V
I_{DSS}	Zero gate voltage drain current	$V_{DS} = 1200V, V_{GS} = 0V$	—	0.1	20	μA
		$V_{DS} = 1200V, V_{GS} = 0V, T_J = 175\text{ }^\circ\text{C}$	—	1.0	—	
I_{GSS}	Gate-source leakage current	$V_{GS} = 20V/-10V$	—	—	± 100	nA

Note:

1. Pulse test: pulse width $< 380\text{ }\mu\text{s}$, duty cycle $< 2\%$.

The following table shows the dynamic characteristics of this device. $T_J = 25\text{ }^{\circ}\text{C}$ unless otherwise specified. The dynamic characteristics are characterized, not 100% tested, at the recommended operating $V_{GS} = 20\text{V}/-5\text{V}$.

Table 1-4. Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{GS} = 0\text{V}$, $V_{DD} = 1360\text{V}$, $V_{AC} = 25\text{ mV}$, $f = 200\text{ kHz}$	—	171	—	pF
C_{rss}	Reverse transfer capacitance		—	1.0	—	
C_{oss}	Output capacitance		—	15	—	
Q_G	Total gate charge	$V_{GS} = -5\text{V}/20\text{V}$, $V_{DD} = 1200\text{V}$, $I_D = 2.5\text{A}$	—	10.1	—	nC
Q_{GS}	Gate-source charge		—	1.9	—	
Q_{GD}	Gate-drain charge		—	3.4	—	
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 1200\text{V}$, $V_{GS} = -5\text{V}/20\text{V}$, $I_D = 5\text{A}$, $R_{G(ext)} = 8\Omega$, Freewheeling diode = MSC750SMA170SD ($V_{GS} = -5\text{V}$); reference Figure 1-19	—	13	—	ns
t_r	Voltage rise time		—	12	—	
$t_{d(off)}$	Turn-off delay time		—	7.0	—	
t_f	Voltage fall time		—	8.0	—	μJ
E_{on}	Turn-on switching energy		—	146	—	
E_{off}	Turn-off switching energy		—	18	—	
ESR	Gate equivalent series resistance	$f = 1\text{ MHz}$, 25 mV , drain short	—	2.89	—	Ω
SCWT	Short circuit withstand time	$V_{DS} = 1200\text{V}$, $V_{GS} = 20\text{V}$	—	2.5	—	μs
E_{AS}	Avalanche energy, single pulse	$I_D = 2.5\text{A}$	—	350	—	mJ

The following table shows the body diode characteristics of this device. $T_J = 25\text{ }^{\circ}\text{C}$ unless otherwise specified. The body diode reverse recovery is characterized, not 100% tested.

Table 1-5. Body Diode Characteristics

Symbol	Characteristic	Test Conditions	Min.	Typ.	Max.	Unit
V_{SD}	Diode forward voltage	$I_{SD} = 2.5\text{A}$, $V_{GS} = 0\text{V}$	—	3.78	—	V
		$I_{SD} = 2.5\text{A}$, $V_{GS} = -5\text{V}$	—	3.84	5.0	
t_{rr}	Reverse recovery time	$I_{SD} = 5\text{A}$, $V_{GS} = -5\text{V}$, Drive $R_G = 8\Omega$, $V_{DD} = 1200\text{V}$, $dI/dt = -5100\text{ A}/\mu\text{s}$	—	8.0	—	ns
Q_{rr}	Reverse recovery charge		—	128	—	nC
I_{RRM}	Reverse recovery current		—	22	—	A

1.3 Typical Performance Curves

Data for performance curves are characterized, not 100% tested.

Figure 1-1. Drain Current vs. V_{DS} at T_J




Figure 1-2. Drain Current vs. V_{DS} at V_{GS}




Figure 1-3. Drain Current vs. V_{DS} at V_{GS}




Figure 1-4. Drain Current vs. V_{DS} at V_{GS}




Figure 1-5. $R_{DS(on)}$ vs. Junction Temperature




Figure 1-6. Gate Charge Characteristics




Figure 1-7. Capacitance vs. Drain-to-Source Voltage




Figure 1-8. Output Charge vs. Drain-to-Source Voltage




Figure 1-9. Output Stored Energy vs. V_{DS}




Figure 1-10. I_D vs. V_{DS} 3rd Quadrant Conduction




Figure 1-11. I_D vs. V_{DS} 3rd Quadrant Conduction




Figure 1-12. Switching Energy E_{on} vs. V_{DS} & I_D




Figure 1-13. Switching Energy E_{off} vs. V_{DS} & I_D




Figure 1-14. Switching Energy vs. R_G




Figure 1-15. Switching Energy vs. Junction Temperature




Figure 1-16. Threshold Voltage vs. Junction Temperature




Figure 1-17. Forward Safe Operating Area






Figure 1-18. Maximum Transient Thermal Impedance



The following figure shows the switching waveform diagram of this device.

Figure 1-19. Switching Waveform




2. Package Specification

This section shows the package specification of this device.

2.1 Package Outline Drawing

The following figure illustrates the TO-263-7L XL package outline of this device.

Figure 2-1. Package Outline Drawing



The following table shows the TO-263-7L XL dimensions and should be used in conjunction with the package outline drawing.

Table 2-1. TO-263-7L XL Dimensions

Symbol	Description	Min. (mm)	Max. (mm)
N	Number of leads	7	
e	Pitch	1.27 BSC	

.....continued

Symbol	Description	Min. (mm)	Max. (mm)
A	Overall height	4.30	4.70
A1	Seating plane height	—	0.25
A2	Seating plane to lead	2.20	2.60
b	Lead width	0.52	0.72
b1		0.60	0.80
c	Lead thickness	0.42	0.62
c2	Thermal pad thickness	1.07	1.47
L	Lead length	4.55	4.95
L1	Tab length	0.87	1.27
L2	Foot length	2.48	2.88
D	Molded body length	9.05	9.45
D1	Thermal pad length	7.58	7.98
E	Total width	9.80	10.20
E1	Thermal pad width step back	6.30	6.70
E2	Thermal pad width	7.80	8.20
Ø	Lead foot angle	0°	8°


Note: Dimensioning and tolerancing per ASME Y14.5M.

- BSC: Basic dimension. Theoretically exact value shown without tolerances.

2.2 Recommended Land Pattern

The following figure illustrates the recommended land pattern of this device.

Figure 2-2. Recommended Land Pattern



The following table shows the recommended land pattern dimensions.

Table 2-2. Recommended Land Pattern Dimensions

Symbol	Description	Min. (mm)	Nom. (mm)	Max. (mm)
E	Contact pitch	1.27 BSC		
X2	Center pad width	—	—	8.30
Y2	Center pad length	—	—	8.45
C1	Contact pad spacing	—	6.45	—
C2	Contact pad spacing	—	4.30	—
X1	Contact pad width (X7)	—	—	0.80
Y1	Contact pad length (X7)	—	—	2.90
G1	Contact pad to center pad (X7)	3.88	—	—
G2	Contact pad to contact pad (X6)	0.47	—	—

Notes:

- Dimensioning and tolerancing per ASME Y14.5M.
 - BSC: Basic dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process.

3. Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

Table 3-1. Revision History

Revision	Date	Description
A	12/2024	Initial revision

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at <https://www.microchip.com/en-us/about/legal-information/microchip-trademarks>.

ISBN: 979-8-3371-0227-6

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip products are strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.