



PM8055 ☆

SXP 48x12G SAS Expander

Status: In Production

[View CAD Symbols](#)

Features:

- SAS-3 T10 zoning for secure storage
- Ultra low switching latency for improved system performance
- SAS and SATA edge-buffering preserves customers' investment by improving performance with existing 3G and 6G drives
- Table-to-table routing removes need for keyed connectors
- Integrated Ethernet port for seamless interface to management entity
- Integrated MIPS processor for enclosure management

[View More](#)



Device Overview

Summary

The SXP 12G 48-port SAS expander features SAS-3 T10 zoning, self-configuration, table-to-table routing, Ethernet port, and an integrated MIPS processor for SES and enclosure management support. All SXP expanders also feature a rich and robust customizable SDK for enclosure management and system level diagnostics and monitoring that offers our customers a clean migration path for their code between product generations.

Additional Features

- SAS-3 T10 zoning for secure storage
- Ultra low switching latency for improved system performance
- SAS and SATA edge-buffering preserves customers' investment by improving performance with existing 3G and 6G drives
- Table-to-table routing removes need for keyed connectors
- Integrated Ethernet port for seamless interface to management entity
- Integrated MIPS processor for enclosure management
- Firmware compatible with Microchip SAS 3 Gbps and 6 Gbps SAS expanders and stand-alone enclosure management controllers
- 12G SAS signaling support for up to 10m mini-SAS HD passive copper cable
- Optical SAS support
- Early power off warning (EPOW) support
- SAS and SATA edge-buffering support
- Ultra-low switching latency to improve system performance
- Quad SPI or parallel flash support; optional inline ECC on the parallel flash
- T10 zoning support (up to 256 zones)
- Port mirroring for system debug
- Local bus data integrity protection
- Real-time eye capture with enhanced BER eye mask and estimation
- Non-disruptive zero down time firmware update support
- Position-independent firmware image support to simplify firmware image management/download
- Compatible enclosure management firmware architecture with SXP 3G/6G products
- Real-time clock (1 μ S counter up to 35+ years)
- Enhanced processing subsystem (MIPS 34Kc at 600 MHz)
- Backward-compatibility with Microchip's 6G/3G SXP devices

High-Speed I/O

- SAS-3 (12 Gbps, 6 Gbps, 3 Gbps, 1.5 Gbps) and SATA-3 (6 Gbps, 3 Gbps, 1.5 Gbps) operation
- Support for up to 4K SAS addresses
- Automated decision feedback equalizer (DFE) per SAS-3
- Programmable continuous time linear equalizer for SATA-3
- Supports spread-spectrum clocking (SSC) per SAS/SATA-3
- Per-PHY configurable transmit and receive SSC
- Per-PHY programmable transmit amplitude and emphasis
- Integrated resistive termination
- SAS 3.0-compliant back-channel training (SAS3 speed negotiation) Peripheral Interfaces

Peripheral Interfaces

- 4 UART interfaces for system monitoring and debugging
- 4 SGPIO interfaces (or additional TWI per SFF-8448)
- Up to 81 GPIO pins
- Eight dedicated two-wire interfaces (up to twelve total) for device configuration and control of external interfaces
- 16-bit local bus interface for connecting to NOR flash and SRAM
- SPI, DSPI, and QSPI interface
- 10/100 Ethernet MAC port
- JTAG and EJTAG interface

Statistics and Performance Monitoring

- Per-port error counters for comprehensive diagnostic capability
- Programmable PMON counters and interrupt generation
- Per-link PRBS and CJPAT pattern generators and loop-backs for link integrity diagnostics
- Real-time clock

Firmware Development Kit

- Zoning configuration interface
- SAM4/SPC4/SES3-compatible SES target with Enclosure Management Application reference design
- SAS-3-compatible protocol stack in virtual SAS/SMP port
- SSP/STP Initiator API supports communication with SSP/STP targets over SAS links
- SMP routing management including topology discovery
- Firmware download over multiple in-band and out-of-band interfaces
- Expander diagnostics API
- Disk spin-up control and disk qualification API
- Peripheral drivers for TWI, UART, SGPIO, and Ethernet interfaces
- TCP/IP enables management of the SXP 12G through remote network
- Error detection, logging, and reporting
- Wake up system through Ethernet or SAS port

Chiplink Diagnostic Utility

- Supports advanced features for validation, characterization, and debugging of Microchip expanders
- Includes full SAS tool suite and a macro interface for user-authored animation scripts

Third Party Support

- Green Hills MULTI development environment and EJTAG debugger

Parameters

Name	Value
Product Type	SAS Expander
Port Count	48
Generation	12 Gbps
Physical Dimensions	31 mm x 31 mm



PM8055 ☆

SXP 48x12G SAS Expander

Status: In Production

 View CAD Symbols

Features:

- SAS-3 T10 zoning for secure storage
- Ultra low switching latency for improved system performance
- SAS and SATA edge-buffering preserves customers' investment by improving performance with existing 3G and 6G drives
- Table-to-table routing removes need for keyed connectors
- Integrated Ethernet port for seamless interface to management entity
- Integrated MIPS processor for enclosure management

[View More](#)



 Overview

 Documents

 Development Environment

 RoHS Information

 Add to Cart

RoHS Information

Part Number	Device Weight (g)	Shipping Weight (Kg)	Lead Count	Package Type	Package Dimension	Solder Composition	JEDEC Indicator	RoHS	China EFUP
PM8055B-FEI	7.423400	12.81481	1408	BFBGA	31x31x2.83mm	SAC305	e1		
PM8055B-FEI-SW1	7.423400	12.81481	1408	BFBGA	31x31x2.83mm	SAC305	e1		

To see a complete listing of RoHS data for this device, please [Click here](#)

Shipping Weight = Device Weight + Packing Material weight. Please [contact sales](#) office if device weight is not available.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[PM8055B-FEI](#)