NPN Switching Transistor
MMBT4401M3T5G

The MMBT4401M3T5G device is a spin−off of our popular SOT−23 three−leaded device. It is designed for general purpose switching applications and is housed in the SOT−723 surface mount package. This device is ideal for low−power surface mount applications where board space is at a premium.



Features

- Reduces Board Space
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant



SOT−723
CASE 631AA
STYLE 1

MARKING DIAGRAM

AF = Specific Device Code
M = Date Code

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	40	Vdc
Collector−Base Voltage	V_{CBO}	60	Vdc
Emitter−Base Voltage	V_{EBO}	6.0	Vdc
Collector Current − Continuous	I_C	600	mAdc

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR−5 Board (Note 1) T_A = 25°C Derate above 25°C	P_D	 265 2.1	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	470	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) T_A = 25°C Derate above 25°C	P_D	640 5.1	mW mW/°C
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	195	°C/W
Junction and Storage Temperature	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. FR−5 = 1.0 × 0.75 × 0.062 in.
2. Alumina = 0.4 × 0.3 × 0.024 in. 99.5% alumina.

ORDERING INFORMATION

Device	Package	Shipping†
MMBT4401M3T5G	SOT−723 (Pb−Free)	8000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2012

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Max	Unit
OFF CHARACTERISTICS					
Collector−Emitter Breakdown Voltage (Note 3)	(I_C = 1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	40	–	Vdc
Collector−Base Breakdown Voltage	(I_C = 0.1 mAdc, I_E = 0)	$V_{(BR)CBO}$	60	–	Vdc
Emitter−Base Breakdown Voltage	(I_E = 0.1 mAdc, I_C = 0)	$V_{(BR)EBO}$	6.0	–	Vdc
Base Cutoff Current	(V_{CE} = 35 Vdc, V_{EB} = 0.4 Vdc)	I_{BEV}	–	0.1	μAdc
Collector Cutoff Current	(V_{CE} = 35 Vdc, V_{EB} = 0.4 Vdc)	I_{CEX}	–	0.1	μAdc
ON CHARACTERISTICS (Note 3)					
DC Current Gain		h_{FE}			–
	(I_C = 0.1 mAdc, V_{CE} = 1.0 Vdc)		20	–	
	(I_C = 1.0 mAdc, V_{CE} = 1.0 Vdc)		40	–	
	(I_C = 10 mAdc, V_{CE} = 1.0 Vdc)		80	–	
	(I_C = 150 mAdc, V_{CE} = 1.0 Vdc)		100	300	
	(I_C = 500 mAdc, V_{CE} = 2.0 Vdc)		40	–	
Collector−Emitter Saturation Voltage		$V_{CE(sat)}$			Vdc
	(I_C = 150 mAdc, I_B = 15 mAdc)		–	0.4	
	(I_C = 500 mAdc, I_B = 50 mAdc)		–	0.75	
Base−Emitter Saturation Voltage		$V_{BE(sat)}$			Vdc
	(I_C = 150 mAdc, I_B = 15 mAdc)		0.75	0.95	
	(I_C = 500 mAdc, I_B = 50 mAdc)		–	1.2	
SMALL−SIGNAL CHARACTERISTICS					
Current−Gain − Bandwidth Product	(I_C = 20 mAdc, V_{CE} = 10 Vdc, f = 100 MHz)	f_T	250	–	MHz
Collector−Base Capacitance	(V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	C_{cb}	–	6.5	pF
Emitter−Base Capacitance	(V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{eb}	–	30	pF
Input Impedance	(I_C = 1.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)	h_{ie}	1.0	15	kΩ
Voltage Feedback Ratio	(I_C = 1.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)	h_{re}	0.1	8.0	X 10^{-4}
Small−Signal Current Gain	(I_C = 1.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)	h_{fe}	40	500	–
Output Admittance	(I_C = 1.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz)	h_{oe}	1.0	30	μmhos
SWITCHING CHARACTERISTICS					
Delay Time	(V_{CC} = 30 Vdc, V_{EB} = 2.0 Vdc, I_C = 150 mAdc, I_{B1} = 15 mAdc)	t_d	–	15	ns
Rise Time		t_r	–	20	
Storage Time	(V_{CC} = 30 Vdc, I_C = 150 mAdc, I_{B1} = I_{B2} = 15 mAdc)	t_s	–	225	ns
Fall Time		t_f	–	30	

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUITS





Scope rise time < 4.0 ns
*Total shunt capacitance of test jig connectors, and oscilloscope

Figure 1. Turn−On Time

Figure 2. Turn−Off Time



Figure 3. DC Current Gain



Figure 4. Collector Saturation Region



Figure 5. Collector−Emitter Saturation Voltage vs. Collector Current



Figure 6. Temperature Coefficients



Figure 7. Base−Emitter Saturation Voltage vs. Collector Current



Figure 8. Base−Emitter Turn On Voltage vs. Collector Current



Figure 9. Input Capacitance vs. Emitter Base Voltage



Figure 10. Output Capacitance vs. Collector Base Voltage



Figure 11. Safe Operating Area



SOT−723 1.20x0.80x0.50, 0.40P
CASE 631AA
ISSUE E

DATE 24 JAN 2024

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.45	0.50	0.55
b	0.15	0.21	0.27
b1	0.25	0.31	0.37
c	0.07	0.12	0.17
D	1.15	1.20	1.25
E	0.75	0.80	0.85
e	0.40 BSC		
H	1.15	1.20	1.25
L	0.29 REF		
L2	0.15	0.20	0.25



TOP VIEW



SIDE VIEW



BOTTOM VIEW



RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

STYLE 1:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 2:
PIN 1. ANODE
2. N/C
3. CATHODE

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. GATE
2. SOURCE
3. DRAIN

DOCUMENT NUMBER:	98AON12989D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	SOT−723 1.20x0.80x0.50, 0.40P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales