

# 2.5 V/3.3 V/5.0 V Differential Data/Clock D Flip-Flop with Reset

Multi-Level Inputs to LVPECL Translator w/ Internal Termination

## NB4L52

The NB4L52 is a differential Data and Clock D flip-flop with a differential asynchronous Reset. The differential inputs incorporate internal 50  $\Omega$  termination resistors and will accept PECL, LVPECL, LVCMOS, LVTTTL, CML, or LVDS logic levels. When Clock transitions from Low to High, Data will be transferred to the differential LVPECL outputs. The differential Clock inputs allow the NB4L52 to also be used as a negative edge triggered device. The device is housed in a small 3x3 mm 16 pin QFN package.

### Features

- Maximum Input Clock Frequency > 4 GHz Typical
- 330 ps Typical Propagation Delay
- 145 ps Typical Rise and Fall Times
- Differential LVPECL Outputs, 750 mV Peak-to-Peak, Typical
- Operating Range:  $V_{CC} = 2.375$  V to 5.5 V with  $V_{EE} = 0$  V
- Internal Input Termination Resistors, 50  $\Omega$
- Functionally Compatible with Existing 2.5 V/3.3 V/5.0 V LVPECL, LVEP, EP, and SG Devices
- $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  Ambient Operating Temperature
- These are Pb-Free Devices





Figure 2. Pinout (Top View)



QFN-16  
MN SUFFIX  
CASE 485G

### MARKING DIAGRAM\*



A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
■ = Pb-Free Package

(Note: Microdot may be in either location)

\*For additional marking information, refer to Application Note [AND8002/D](#).




Figure 1. Logic Diagram

Table 1. TRUTH TABLE

| R | D | CLK | Q |
|---|---|-----|---|
| H | x | x   | L |
| L | L | Z   | L |
| L | H | Z   | H |

Z = LOW to HIGH Transition

x = Don't Care

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

## NB4L52

**Table 2. PIN DESCRIPTION**

| Pin | Name                  | I/O                                  | Description                                                                                                                                                                                                                                                                 |
|-----|-----------------------|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | $V_{TD}$              | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| 2   | D                     | ECL, CML, LVCMOS, LVDS, LVTTTL Input | Noninverted Differential Input. (Note 1)                                                                                                                                                                                                                                    |
| 3   | $\bar{D}$             | ECL, CML, LVCMOS, LVDS, LVTTTL Input | Inverted Differential Input. (Note 1)                                                                                                                                                                                                                                       |
| 4   | $\overline{V_{TD}}$   | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| 5   | $V_{TCLK}$            | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| 6   | CLK                   | ECL, CML, LVCMOS, LVDS, LVTTTL Input | Noninverted Differential Input. (Note 1)                                                                                                                                                                                                                                    |
| 7   | $\overline{CLK}$      | ECL, CML, LVCMOS, LVDS, LVTTTL Input | Inverted Differential Input. (Note 1)                                                                                                                                                                                                                                       |
| 8   | $\overline{V_{TCLK}}$ | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| 9   | $V_{EE}$              | –                                    | Negative Supply Voltage                                                                                                                                                                                                                                                     |
| 10  | $\bar{Q}$             | ECL Output                           | Inverted Differential Output. Typically terminated with 50 $\Omega$ resistor to $V_{CC} - 2.0$ V.                                                                                                                                                                           |
| 11  | Q                     | ECL Output                           | Noninverted Differential Output. Typically terminated with 50 $\Omega$ resistor to $V_{CC} - 2.0$ V.                                                                                                                                                                        |
| 12  | $V_{CC}$              | –                                    | Positive Supply Voltage                                                                                                                                                                                                                                                     |
| 13  | $V_{TR}$              | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| 14  | R                     | LVECL, LVCMOS, LVTTTL Input          | Noninverted Differential Reset Input. (Note 1)                                                                                                                                                                                                                              |
| 15  | $\bar{R}$             | LVECL, LVCMOS, LVTTTL Input          | Inverted Differential Reset Input. (Note 1)                                                                                                                                                                                                                                 |
| 16  | $\overline{V_{TR}}$   | –                                    | Internal 50 $\Omega$ Termination Pin. (See Table 4)                                                                                                                                                                                                                         |
| –   | EP                    | –                                    | The Exposed Pad (EP) on the QFN–16 package bottom is thermally connected to the die for improved heat transfer out of package. The pad is not electrically connected to the die, but is recommended to be electrically and thermally connected to $V_{EE}$ on the PC board. |

1. In the differential configuration when the input termination pin ( $V_{TD}$ ,  $\overline{V_{TD}}$ ,  $V_{TR}$ ,  $\overline{V_{TR}}$ ,  $V_{TCLK}$ ,  $\overline{V_{TCLK}}$ ) are connected to a common termination voltage or left open, and if no signal is applied on D/ $\bar{D}$ , CLK/ $\overline{CLK}$ , R/ $\bar{R}$  input then the device will be susceptible to self-oscillation.

**Table 3. ATTRIBUTES**

| Characteristic                                         | Value                |             |
|--------------------------------------------------------|----------------------|-------------|
| ESD Protection                                         | Human Body Model     | > 2 kV      |
|                                                        | Machine Model        | > 200 V     |
|                                                        | Charged Device Model | > 1 kV      |
| Moisture Sensitivity (Note 2)                          | Pb Pkg               | Pb-Free Pkg |
| QFN-16                                                 | Level 1              | Level 1     |
| Flammability Rating Oxygen Index: 28 to 34             | UL 94 V-0 @ 0.125 in |             |
| Transistor Count                                       | 164                  |             |
| Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test |                      |             |

2. For additional information, see Application Note AND8003/D.

Table 4. MAXIMUM RATINGS

| Symbol           | Parameter                                            | Condition 1                                    | Condition 2                                                          | Rating      | Unit         |
|------------------|------------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|-------------|--------------|
| V <sub>CC</sub>  | Positive Power Supply                                | V <sub>EE</sub> = 0 V                          |                                                                      | 6.0         | V            |
| V <sub>EE</sub>  | Negative Power Supply                                | V <sub>CC</sub> = 0 V                          |                                                                      | -6.0        | V            |
| V <sub>IO</sub>  | Positive Input/Output<br>Negative Input/Output       | V <sub>EE</sub> = 0 V<br>V <sub>CC</sub> = 0 V | V <sub>I</sub> ≤ V <sub>CC</sub><br>V <sub>I</sub> ≥ V <sub>EE</sub> | 6.0<br>-6.0 | V<br>V       |
| I <sub>IN</sub>  | Input Current Through R <sub>T</sub> (50 Ω Resistor) | Static<br>Surge                                |                                                                      | 45<br>80    | mA<br>mA     |
| I <sub>out</sub> | Output Current                                       | Continuous<br>Surge                            |                                                                      | 25<br>50    | mA<br>mA     |
| T <sub>A</sub>   | Operating Temperature Range                          |                                                |                                                                      | -40 to +85  | °C           |
| T <sub>stg</sub> | Storage Temperature Range                            |                                                |                                                                      | -65 to +150 | °C           |
| θ <sub>JA</sub>  | Thermal Resistance (Junction-to-Ambient)             | 0 LFPM<br>500 LFPM                             | 16 QFN<br>16 QFN                                                     | 42<br>35    | °C/W<br>°C/W |
| θ <sub>JC</sub>  | Thermal Resistance (Junction-to-Case)                | 2S2P (Note 3)                                  | 16 QFN                                                               | 4.0         | °C/W         |
| T <sub>sol</sub> | Wave Solder<br>Pb-Free                               |                                                |                                                                      | 265         | °C           |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

3. JEDEC standard multilayer board – 2S2P (2 signal, 2 power) with 8 filled thermal vias under exposed pad.

Table 5. DC CHARACTERISTICS, CLOCK INPUTS, LVPECL OUTPUTS

(V<sub>CC</sub> = 2.375 V to 5.5 V, V<sub>EE</sub> = 0 V or V<sub>CC</sub> = 0 V, V<sub>EE</sub> = -2.375 to -5.5 V, T<sub>A</sub> = -40°C to +85°C)

| Symbol          | Characteristic                                                                                                   | Min                                            | Typ                                            | Max                                           | Unit |
|-----------------|------------------------------------------------------------------------------------------------------------------|------------------------------------------------|------------------------------------------------|-----------------------------------------------|------|
| I <sub>EE</sub> | Power Supply Current (Inputs and Outputs Open)                                                                   | –                                              | 16                                             | 25                                            | mA   |
| V <sub>OH</sub> | Output HIGH Voltage (Note 4, 5)<br>V <sub>CC</sub> = 5.0 V<br>V <sub>CC</sub> = 3.3 V<br>V <sub>CC</sub> = 2.5 V | V <sub>CC</sub> – 1145<br>3855<br>2155<br>1355 | V <sub>CC</sub> – 1020<br>3980<br>2280<br>1480 | V <sub>CC</sub> – 895<br>4105<br>2405<br>1605 | mV   |
| V <sub>OL</sub> | Output LOW Voltage (Note 4, 5)<br>V <sub>CC</sub> = 5.0V<br>V <sub>CC</sub> = 3.3V<br>V <sub>CC</sub> = 2.5V     | V <sub>CC</sub> – 1945<br>3055<br>1355<br>555  | V <sub>CC</sub> – 1770<br>3230<br>1530<br>730  | V <sub>CC</sub> – 1600<br>3400<br>1700<br>900 | mV   |

#### DIFFERENTIAL INPUT DRIVEN SINGLE-ENDED (Figures 4 & 7)

|                 |                                                  |                       |   |                       |    |
|-----------------|--------------------------------------------------|-----------------------|---|-----------------------|----|
| V <sub>th</sub> | Input Threshold Reference Voltage Range (Note 6) | 1050                  | – | V <sub>CC</sub> – 150 | mV |
| V <sub>IH</sub> | Single-ended Input HIGH Voltage                  | V <sub>th</sub> + 150 | – | V <sub>CC</sub>       | mV |
| V <sub>IL</sub> | Single-ended Input LOW Voltage                   | V <sub>EE</sub>       | – | V <sub>th</sub> – 150 | mV |

#### DIFFERENTIAL INPUT DRIVEN DIFFERENTIALLY (Figures 5, 6 & 8)

|                  |                                                                                     |                 |    |                       |    |
|------------------|-------------------------------------------------------------------------------------|-----------------|----|-----------------------|----|
| V <sub>IHD</sub> | Differential Input HIGH Voltage                                                     | 1200            | –  | V <sub>CC</sub>       | mV |
| V <sub>ILD</sub> | Differential Input LOW Voltage                                                      | V <sub>EE</sub> | –  | V <sub>CC</sub> – 150 | mV |
| V <sub>CMR</sub> | Input Common Mode Range (Differential Configuration) (Note 7)                       | 1125            | –  | V <sub>CC</sub> – 75  | mV |
| V <sub>ID</sub>  | Differential Input Voltage (V <sub>IHD</sub> – V <sub>ILD</sub> )                   | 150             | –  | V <sub>CC</sub>       | mV |
| I <sub>IH</sub>  | Input HIGH Current D / $\bar{D}$ , CLK / $\bar{CLK}$ , R / $\bar{R}$ (VTx/VTx Open) | –150            | –  | 150                   | μA |
| I <sub>IL</sub>  | Input LOW Current D / $\bar{D}$ , CLK / $\bar{CLK}$ , R / $\bar{R}$ (VTx/VTx Open)  | –150            | –  | 150                   | μA |
| R <sub>TIN</sub> | Internal Input Termination Resistor                                                 | 40              | 50 | 60                    | Ω  |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm.

4. LVPECL outputs loaded with 50 Ω to V<sub>CC</sub> – 2.0 V for proper operation.

5. Input and output parameters vary 1:1 with V<sub>CC</sub>.

6. V<sub>th</sub> is applied to the complementary input when operating in single-ended mode.

7. V<sub>CMRMIN</sub> varies 1:1 with V<sub>EE</sub>, V<sub>CMRMAX</sub> varies 1:1 with V<sub>CC</sub>. The V<sub>CMR</sub> range is referenced to the most positive side of the differential input signal.


# NB4L52

**Table 6. AC CHARACTERISTICS**  $V_{CC} = 2.375 \text{ V to } 5.5 \text{ V}$ ;  $V_{EE} = 0 \text{ V or } V_{CC} = 0 \text{ V}$ ,  $V_{EE} = -2.375 \text{ to } -5.5 \text{ V}$  (Note 8)

| Symbol                   | Characteristic                                                                                                                                                             | -40°C |     |      | 25°C |     |      | 85°C |     |      | Unit |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----|------|------|-----|------|------|-----|------|------|
|                          |                                                                                                                                                                            | Min   | Typ | Max  | Min  | Typ | Max  | Min  | Typ | Max  |      |
| $V_{OUTPP}$              | Output Voltage Amplitude (@ $V_{INPPmin}$ )<br>(Note 10) (See Figure 4)<br>$f_{in} \leq 2.0 \text{ GHz}$<br>$f_{in} \leq 3.0 \text{ GHz}$<br>$f_{in} \leq 4.0 \text{ GHz}$ | 530   | 770 | –    | 530  | 780 | –    | 530  | 760 | –    | mV   |
|                          |                                                                                                                                                                            | 490   | 720 | –    | 490  | 730 | –    | 490  | 680 | –    |      |
|                          |                                                                                                                                                                            | 380   | 580 | –    | 380  | 580 | –    | 380  | 530 | –    |      |
| $t_{PLH}$ ,<br>$t_{PHL}$ | Propagation Delay to CLK to Q, R to Q<br>Output Differential                                                                                                               | 300   | 400 | 500  | 300  | 400 | 500  | 300  | 400 | 500  | ps   |
| $t_s$                    | Setup Time                                                                                                                                                                 | 100   | –   | –    | 100  | –   | –    | 100  | –   | –    | ps   |
| $t_h$                    | Hold Time                                                                                                                                                                  | 50    | –   | –    | 50   | –   | –    | 50   | –   | –    | ps   |
| $t_{RR}$                 | Reset Recovery                                                                                                                                                             | 400   | –   | –    | 400  | –   | –    | 400  | –   | –    | ps   |
| $t_{PW}$                 | Minimum Pulse Width R/R                                                                                                                                                    | 250   | –   | –    | 250  | –   | –    | 250  | –   | –    | ps   |
| $t_{JITTER}$             | RMS Random Clock Jitter (Note 9)<br>$f_{in} \leq 2.0 \text{ GHz}$<br>$f_{in} \leq 3.0 \text{ GHz}$<br>$f_{in} \leq 4.0 \text{ GHz}$                                        | –     | 1   | –    | –    | 1   | –    | –    | 1   | –    | ps   |
|                          |                                                                                                                                                                            | –     | 1   | –    | –    | 1   | –    | –    | 1   | –    |      |
|                          |                                                                                                                                                                            | –     | 1   | –    | –    | 1   | –    | –    | 1   | –    |      |
| $V_{INPP}$               | Input Voltage Swing/Sensitivity<br>(Differential Configuration) (Note 10)                                                                                                  | 150   | –   | 2800 | 150  | –   | 2800 | 150  | –   | 2800 | mV   |
| $t_r$ ,<br>$t_f$         | Output Rise/Fall Times @ 0.5 GHz<br>(20% – 80%)                                                                                                                            | 80    | 135 | 190  | 80   | 145 | 190  | 80   | 155 | 190  | ps   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm.

8. Measured by forcing  $V_{INPP}$  (MIN) from a 50% duty cycle clock source. All loading with an external  $R_L = 50 \Omega$  to  $V_{CC} - 2.0 \text{ V}$ . Input edge rates 40 ps (20% – 80%).
9. Additive RMS jitter with 50% duty cycle clock signal.
10. Input and output voltage swing is a single-ended measurement operating in differential mode.



**Figure 3. Output Voltage Amplitude ( $V_{OUTPP}$ ) vs. Clock Input Frequency at Ambient Temperature (Typical).**

# NB4L52




Figure 4. Differential Input Driven Single-Ended




Figure 5. Differential Inputs Driven Differentially




Figure 6. Differential Inputs Driven Differentially




Figure 7.  $V_{th}$  Diagram




Figure 8.  $V_{CMR}$  Diagram





Figure 9. AC Reference Measurement

## NB4L52



**Figure 10. Typical Termination for Output Driver and Device Evaluation**  
 (See Application Note AND8020/D – Termination of ECL Logic Devices.)

### ORDERING INFORMATION

| Device      | Package                    | Shipping <sup>†</sup> |
|-------------|----------------------------|-----------------------|
| NB4L52MNG   | QFN-16, 3 x 3 mm (Pb-Free) | 123 Units / Rail      |
| NB4L52MNR2G | QFN-16, 3 x 3 mm (Pb-Free) | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).

### Resource Reference of Application Notes

- AN1405/D** – ECL Clock Distribution Techniques
- AN1406/D** – Designing with PECL (ECL at +5.0 V)
- AN1503/D** – ECLinPS I/O SPiCE Modeling Kit
- AN1504/D** – Metastability and the ECLinPS Family
- AN1568/D** – Interfacing Between LVDS and ECL
- AN1672/D** – The ECL Translator Guide
- AND8001/D** – Odd Number Counters Design
- AND8002/D** – Marking and Date Codes
- AND8020/D** – Termination of ECL Logic Devices
- AND8066/D** – Interfacing with ECLinPS
- AND8090/D** – AC Characteristics of ECL Devices




The products described herein (NB4L52), may be covered by U.S. patents including 6,362,644. There may be other patents pending.



SCALE 2:1



**QFN16 3x3, 0.5P**  
CASE 485G  
ISSUE G

DATE 08 OCT 2021





## NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.


DETAIL B  
ALTERNATE  
CONSTRUCTIONS

DETAIL A  
ALTERNATE TERMINAL  
CONSTRUCTIONS

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.80        | 0.90 | 1.00 |
| A1  | 0.00        | 0.03 | 0.05 |
| A3  | 0.20 REF    |      |      |
| b   | 0.18        | 0.24 | 0.30 |
| D   | 3.00 BSC    |      |      |
| D2  | 1.65        | 1.75 | 1.85 |
| E   | 3.00 BSC    |      |      |
| E2  | 1.65        | 1.75 | 1.85 |
| e   | 0.50 BSC    |      |      |
| k   | 0.18 TYP    |      |      |
| L   | 0.30        | 0.40 | 0.50 |
| L1  | 0.00        | 0.08 | 0.15 |

## MOUNTING FOOTPRINT


**GENERIC  
MARKING DIAGRAM\***


XXXXX = Specific Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                         |                        |                                                                                                                                                                                  |
|-------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON04795D</b>     | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>QFN16 3X3, 0.5P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)