MJE2955T (PNP), MJE3055T (NPN)

Complementary Silicon Plastic Power Transistors

These devices are designed for use in general−purpose amplifier and switching applications.

Features

- High Current Gain − Bandwidth Product
- These Devices are Pb−Free and are RoHS Compliant*

ON Semiconductor®

www.onsemi.com

10 AMPERE COMPLEMENTARY SILICON POWER TRANSISTORS 60 VOLTS − 75 WATTS

PNP



NPN





TO−220
CASE 221A−09
STYLE 1

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	60	Vdc
Collector−Base Voltage	V_{CB}	70	Vdc
Emitter−Base Voltage	V_{EB}	5.0	Vdc
Collector Current	I_C	10	Adc
Base Current	I_B	6.0	Adc
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D (Note 1)	75 0.6	W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Safe Area Curves are indicated by Figure 1. Both limits are applicable and must be observed.

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	1.67	°C/W

MARKING DIAGRAM



MJExx55T = Device Code
xx = 29 or 30
G = Pb−Free Package
A = Assembly Location
Y = Year
WW = Work Week

ORDERING INFORMATION

Device	Package	Shipping
MJE2955TG	TO−220 (Pb−Free)	50 Units / Rail
MJE3055TG	TO−220 (Pb−Free)	50 Units / Rail

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2015

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (Note 2) (I_C = 200 mAdc, I_B = 0)	$V_{CEO(sus)}$	60	–	Vdc
Collector Cutoff Current (V_{CE} = 30 Vdc, I_B = 0)	I_{CEO}	–	700	μAdc
Collector Cutoff Current (V_{CE} = 70 Vdc, $V_{EB(off)}$ = 1.5 Vdc) (V_{CE} = 70 Vdc, $V_{EB(off)}$ = 1.5 Vdc, T_C = 150°C)	I_{CEX}	– –	1.0 5.0	mAdc
Collector Cutoff Current (V_{CB} = 70 Vdc, I_E = 0) (V_{CB} = 70 Vdc, I_E = 0, T_C = 150°C)	I_{CBO}	– –	1.0 10	mAdc
Emitter Cutoff Current (V_{BE} = 5.0 Vdc, I_C = 0)	I_{EBO}	–	5.0	mAdc
ON CHARACTERISTICS				
DC Current Gain (Note 2) (I_C = 4.0 Adc, V_{CE} = 4 0 Vdc) (I_C = 10 Adc, V_{CE} = 4.0 Vdc)	h_{FE}	20 5.0	100 –	–
Collector−Emitter Saturation Voltage (Note 2) (I_C = 4.0 Adc, I_B = 0.4 Adc) (I_C = 10 Adc, I_B = 3.3 Adc)	$V_{CE(sat)}$	– –	1.1 8.0	Vdc
Base−Emitter On Voltage (Note 2) (I_C = 4.0 Adc, V_{CE} = 4.0 Vdc)	$V_{BE(on)}$	–	1.8	Vdc
DYNAMIC CHARACTERISTICS				
Current−Gain−Bandwidth Product (I_C = 500 mAdc, V_{CE} = 10 Vdc, f = 500 kHz)	f_T	2.0	–	MHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 20%.



Figure 1. Active−Region Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 1 is based on $T_{J(pk)}$ = 150°C. T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



Figure 2. DC Current Gain



Figure 3. Power Derating



Figure 4. “On” Voltages

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales