Field Stop Trench IGBT, 30 A, 650 V

FGAF30S65AQ

Using novel field stop IGBT technology, ON Semiconductor's new series of field stop 4th generation of RC IGBTs offer the optimum performance for PFC applications and welder where low conduction and switching losses are essential.

Features

- Maximum Junction Temperature: T_J = 175°C
- Positive Temperature Co−efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(Sat)}$ = 1.4 V (Typ.) @ I_C = 30 A
- 100% of the Parts Tested for I_{LM} (Note 1)
- High Input Impedance
- Fast Switching
- Tighten Parameter Distribution
- IGBT with Monolithic Reverse Conducting Diode
- This Device is Pb−Free and is RoHS Compliant

Typical Applications

- PFC, Welder

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector to Emitter Voltage	V_{CES}	650	V
Gate to Emitter Voltage Transient Gate to Emitter Voltage	V_{GES}	±20 ±30	V
Collector Current @T_C = 25°C @T_C = 100°C	I_C	60 30	A
Pulsed Collector Current (Note 1)	I_{LM}	90	A
Pulsed Collector Current (Note 2)	I_{CM}	90	A
Diode Forward Current @T_C = 25°C @ T_C = 100°C	I_F	30 15	A
Pulsed Diode Maximum Forward Current	I_{FM}	90	A
Maximum Power Dissipation@T_C = 25°C @ T_C = 100°C	P_D	83 42	W
Operating Junction / Storage Temperature Range	T_J, T_{STG}	−55 to +175	°C
Maximum Lead Temp. for Soldering Purposes, 1/8″ from case for 5 seconds	T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. V_{CC} = 400 V, V_{GE} = 15 V, I_C = 90 A, R_G = 13 Ω, Inductive Load, 100% Tested
2. Repetitive rating: pulse width limited by max. Junction temperature

ON Semiconductor®

www.onsemi.com

30 A, 650 V
$V_{CE(sat)}$ = 1.4 V (Typ.)



TO−3PF
CASE 340AH

MARKING DIAGRAM



&Y = ON Semiconductor Logo
&E = Designate space on marking
&3 = 3−Digit Data Code
&K = 2−Digit Lot Traceability Code
FGAF30S65AQ = Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping
FGAF30S65AQ	TO−3PF−3L	30 Units / Rail

© Semiconductor Components Industries, LLC, 2019

Table 1. THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case, for IGBT	$R_{\theta JC}$	1.8	°C/W
Thermal Resistance, Junction−to−Case, for Diode	$R_{\theta JC}$	2.3	°C/W
Thermal Resistance, Junction−to−Case, for Diode	$R_{\theta JA}$	40	°C/W

Table 2. ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTIC						
Collector−emitter breakdown voltage, gate−emitter short−circuited	V_{GE} = 0 V, I_C = 1 mA	BV_{CES}	650	–	–	V
Temperature Coefficient of Breakdown Voltage	V_{GE} = 0 V, I_C = 1 mA	ΔBV_{CES} / ΔT_J	–	0.5	–	V/°C
Collector−emitter cut−off current, gate−emitter short−circuited	V_{GE} = 0 V, V_{CE} = 650 V	I_{CES}	–	–	250	μA
Gate leakage current, collector−emitter short−circuited	V_{GE} = 20 V, V_{CE} = 0 V	I_{GES}	–	–	±400	nA
ON CHARACTERISTIC						
Gate−emitter threshold voltage	V_{GE} = V_{CE}, I_C = 30 mA	$V_{GE(th)}$	2.6	5.3	6.6	V
Collector−emitter saturation voltage	V_{GE} = 15 V, I_C = 30 A V_{GE} = 15 V, I_C = 30 A, T_J = 175°C	$V_{CE(sat)}$	– –	1.4 1.7	2.1 –	V
DYNAMIC CHARACTERISTIC						
Input capacitance	V_{CE} = 30 V, V_{GE} = 0 V, f = 1 MHz	C_{ies}	–	1959	–	pF
Output capacitance		C_{oes}	–	29	–	
Reverse transfer capacitance		C_{res}	–	8	–	
Gate charge total	V_{CE} = 400 V, I_C = 30 A, V_{GE} = 15 V	Q_g	–	58	–	nC
Gate to emitter charge		Q_{ge}	–	13	–	
Gate to collector charge		Q_{gc}	–	17	–	
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD						
Turn−on delay time	T_J = 25°C V_{CC} = 400 V, I_C = 7.5 A R_g = 13 Ω V_{GE} = 15 V Inductive Load	$t_{d(on)}$	–	17.6	–	ns
Rise time		t_r	–	6	–	
Turn−off delay time		$t_{d(off)}$	–	97	–	
Fall time		t_f	–	44	–	
Turn−on switching loss		E_{on}	–	295	–	μJ
Turn−off switching loss		E_{off}	–	82	–	
Total switching loss		E_{ts}	–	377	–	
Turn−on delay time	T_J = 25°C V_{CC} = 400 V, I_C = 15 A R_g = 13 Ω V_{GE} = 15 V Inductive Load	$t_{d(on)}$	–	18	–	ns
Rise time		t_r	–	11	–	
Turn−off delay time		$t_{d(off)}$	–	92	–	
Fall time		t_f	–	24	–	
Turn−on switching loss		E_{on}	–	515	–	μJ
Turn−off switching loss		E_{off}	–	140	–	
Total switching loss		E_{ts}	–	655	–	

Table 2. ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD						
Turn−on delay time	T_J = 175°C V_{CC} = 400 V, I_C = 7.5 A R_g = 13 Ω V_{GE} = 15 V Inductive Load	$t_{d(on)}$	–	17.6	–	ns
Rise time		t_r	–	6.4	–	
Turn−off delay time		$t_{d(off)}$	–	110	–	
Fall time		t_f	–	56	–	
Turn−on switching loss		E_{on}	–	442	–	μJ
Turn−off switching loss		E_{off}	–	145	–	
Total switching loss		E_{ts}	–	587	–	
Turn−on delay time	T_J = 175°C V_{CC} = 400 V, I_C = 15 A R_g = 13 Ω V_{GE} = 15 V Inductive Load	$t_{d(on)}$	–	18	–	ns
Rise time		t_r	–	12	–	
Turn−off delay time		$t_{d(off)}$	–	104	–	
Fall time		t_f	–	48	–	
Turn−on switching loss		E_{on}	–	741	–	μJ
Turn−off switching loss		E_{off}	–	274	–	
Total switching loss		E_{ts}	–	1015	–	
DIODE CHARACTERISTIC						
Forward Voltage	I_F = 15 A I_F = 15 A, T_J = 175°C	V_F	– –	1.3 1.3	1.6 –	V
Reverse Recovery Energy	I_F = 15 A, dI_F/dt = 200 A/μs	E_{rec}	–	239	–	μJ
Diode Reverse Recovery Time	I_F = 15 A, dI_F/dt = 200 A/μs I_F =15 A, dI_F/dt = 200 A/μs, T_J = 175°C	T_{rr}	–	267 347	–	nS
Diode Reverse Recovery Charge	I_F = 15 A, dI_F/dt = 200 A/μs I_F = 15 A, dI_F/dt = 200 A/μs, T_J = 175°C	Q_{rr}	–	1135 1873	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS



Figure 1. Typical Output Characteristics



Figure 2. Typical Output Characteristics



Figure 3. Typical Saturation Voltage Characteristics



Figure 4. Saturation Voltage vs. Case Temperature at Variant Current Level



Figure 5. Saturation Voltage vs. V_{GE}



Figure 6. Saturation Voltage vs. V_{GE}

TYPICAL CHARACTERISTICS



Figure 7. Capacitance Characteristics



Figure 8. Gate Charge



Figure 9. Turn−On Characteristics vs. Gate Resistance



Figure 10. Turn−Off Characteristics vs. Gate Resistance



Figure 11. Switching Loss vs. Gate Resistance



Figure 12. Turn−On Characteristics vs. Collector Current

TYPICAL CHARACTERISTICS



Figure 13. Turn−Off Characteristics vs. Collector Current



Figure 14. Switching Loss vs. Collector Current



Figure 15. Load Current vs. Frequency



Figure 16. SOA Characteristics (FBSOA)



Figure 17. Forward Characteristics



Figure 18. Reverse Recovery Current

TYPICAL CHARACTERISTICS



Figure 19. Reverse Recovery Time



Figure 20. Stored Charge



Figure 21. Transient Thermal Impedance of IGBT



Figure 22. Transient Thermal Impedance of Diode

TO−3PF−3L
CASE 340AH
ISSUE A

DATE 09 JAN 2015



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR UNCONTROLLED IN THIS AREA (6 PLACES).
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR GATE PROTRUSIONS. MOLD FLASH AND GATE PROTRUSIONS NOT TO EXCEED 0.13 PER SIDE. THESE DIMENSIONS ARE TO BE MEASURED AT THE OUTERMOST EXTREME OF THE PLASTIC BODY.
5. DIMENSION b2 DOES NOT INCLUDE DAMBAR PROTRUSION. LEAD WIDTH INCLUDING PROTRUSION SHALL NOT EXCEED 2.20.

	MILLIMETERS	
DIM	MIN	MAX
A	5.30	5.70
A1	2.80	3.20
A2	3.10	3.50
A3	1.80	2.20
b	0.65	0.95
b2	1.90	2.15
b3	3.80	4.20
c	0.80	1.10
D	24.30	24.70
D2	24.70	25.30
D3	3.30	3.70
E	15.30	15.70
e	5.35	5.55
H1	9.80	10.20
L	19.10	19.50
L1	4.80	5.20
L2	1.90	2.20
P	3.40	3.80
Q	4.30	4.70

DOCUMENT NUMBER:	98AON79755E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO−3PF−3L	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales