

# Zener Protection Diode

## NZ8P Series

The NZ8P series of Protection Diodes are designed for applications requiring transient overvoltage ESD protection. They are intended for use to protect voltage sensitive components from ESD and other harmful transient voltage events. This device provides a single channel of uni-directional protection in an ultra-compact X2DFNW2 1.0 x 0.6 mm package.

### Features

- Full Range of Working Voltage Options
- High ESD Ratings
- Wettable Flank Package for Optimal Automated Optical Inspection (AOI)
- SZ Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


### Typical Applications

- Automotive ECU's
- IVN – In Vehicle Networking
- Voltage Sensitive Circuits

### MAXIMUM RATINGS (T<sub>A</sub> = 25 °C unless otherwise noted)

| Rating                                                                                                                                                     | Symbol                            | Value                           | Unit |
|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|---------------------------------|------|
| IEC 61000-4-2 Contact<br>IEC 61000-4-2 Air<br>ISO 10605 Contact (330 pF / 330 Ω)<br>ISO 10605 Contact (330 pF / 2 kΩ)<br>ISO 10605 Contact (150 pF / 2 kΩ) | ESD                               | ±30<br>±30<br>±30<br>±30<br>±30 | kV   |
| Junction and Storage Temperature Range                                                                                                                     | T <sub>J</sub> , T <sub>stg</sub> | –55 to +150                     | °C   |
| Lead Solder Temperature – Maximum<br>(10 Second Duration)                                                                                                  | T <sub>L</sub>                    | 260                             | °C   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



X2DFNW2  
CASE 711BG

### DEVICE MARKING INFORMATION



XX = Specific Device Code  
M = Date Code

### ORDERING INFORMATION

| Device           | Package              | Shipping <sup>†</sup> |
|------------------|----------------------|-----------------------|
| NZ8PxxxMX2WT5G   | X2DFNW2<br>(Pb-Free) | 8000 / Tape<br>& Reel |
| SZNZ8PxxxMX2WT5G |                      |                       |

<sup>†</sup> For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, [BRD8011/D](http://www.onsemi.com/BRD8011/D).


## NZ8P Series

### ELECTRICAL CHARACTERISTICS

( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| Symbol    | Parameter                                   |
|-----------|---------------------------------------------|
| $I_{PP}$  | Maximum Reverse Peak Pulse Current          |
| $V_C$     | Clamping Voltage @ $I_{PP}$                 |
| $V_{RWM}$ | Working Peak Reverse Voltage                |
| $I_R$     | Maximum Reverse Leakage Current @ $V_{RWM}$ |
| $V_{BR}$  | Breakdown Voltage @ $I_T$                   |
| $I_T$     | Test Current                                |

\* See Application Note AND8308/D for detailed explanations of datasheet parameters.



### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Device*        | Device Marking | $V_{RWM}$<br>(Note 1) | $V_{BR} @ I_T = 5 \text{ mA}$<br>(Note 2) |     |      | $V_{BR} @ I_T = 5 \text{ mA}$<br>(150 °C) | $I_R @ V_{RWM}$ |     |      | $V_C \text{ Max @ } I_{PP} = 1.0 \text{ A}$ | $I_{PP} \text{ Max}$<br>(8x20 $\mu\text{s}$ ) | Junction Capacitance<br>Typical |
|----------------|----------------|-----------------------|-------------------------------------------|-----|------|-------------------------------------------|-----------------|-----|------|---------------------------------------------|-----------------------------------------------|---------------------------------|
|                |                | V                     | V                                         |     |      | V                                         | nA              |     |      | V                                           | A                                             | pF                              |
|                |                |                       | Min                                       | Typ | Max  |                                           | Min             | Typ | Max  |                                             |                                               |                                 |
| NZ8P3V3MX2WT5G | P7             | 3.3                   | 3.6                                       | 3.9 | 4.2  | 4.5                                       |                 | 200 | 5000 | 5.5                                         | 8                                             | 109                             |
| NZ8P5V0MX2WT5G | P6             | 5.0                   | 6.0                                       | 6.2 | 6.4  | 7.0                                       |                 | 10  | 1000 | 9                                           | 8                                             | 47                              |
| NZ8P7V0MX2WT5G | PA             | 7.0                   | 8.0                                       | 8.2 | 8.4  | 9.3                                       |                 | 1.5 | 500  | 10                                          | 8                                             | 40                              |
| NZ8P8V0MX2WT5G | PB             | 8.0                   | 9.7                                       | 10  | 10.3 | 11.7                                      |                 | 1   | 100  | 11.5                                        | 8                                             | 40                              |
| NZ8P12VMX2WT5G | P5             | 12                    | 14.5                                      | 15  | 15.4 | 17.5                                      |                 | 1   | 100  | 17                                          | 7                                             | 38                              |
| NZ8P15VMX2WT5G | P4             | 15                    | 17.5                                      | 18  | 18.5 | 21.0                                      |                 | 1   | 100  | 22                                          | 6                                             | 31                              |
| NZ8P18VMX2WT5G | PC             | 18                    | 21.4                                      | 22  | 22.6 | 25.7                                      |                 | 1   | 100  | 26.5                                        | 5                                             | 20                              |
| NZ8P20VMX2WT5G | PD             | 20                    | 23.4                                      | 24  | 24.6 | 28.0                                      |                 | 1   | 100  | 29.5                                        | 5                                             | 20                              |
| NZ8P24VMX2WT5G | P3             | 24                    | 26.3                                      | 27  | 27.7 | 31.2                                      |                 | 1   | 100  | 35                                          | 4.5                                           | 19                              |
| NZ8P26VMX2WT5G | P2             | 26                    | 32.2                                      | 33  | 33.8 | 38.8                                      |                 | 1   | 100  | 38                                          | 4.5                                           | 19                              |
| NZ8P36VMX2WT5G | P8             | 36                    | 38.1                                      | 39  | 39.9 | 45.3                                      |                 | 1   | 100  | 49                                          | 3.0                                           | 15                              |
| NZ8P42VMX2WT5G | P9             | 42                    | 45.5                                      | 47  | 48.5 | 55.1                                      |                 | 1   | 100  | 60                                          | 3.0                                           | 12                              |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

\* Includes SZ prefix where applicable: SZ Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements;


AEC-Q101 Qualified and PPAP Capable.

1. Surge protection devices are normally selected according to the working peak reverse voltage ( $V_{RWM}$ ), which should be equal or greater than the DC or continuous peak operating voltage level.
2.  $V_{BR}$  is measure at pulse test current  $I_T$ .

## NZ8P Series




### REVISION HISTORY

| Revision | Description of Changes | Date       |
|----------|------------------------|------------|
| 0        | Initial Release.       | 06/18/2025 |



**X2DFNW2 1.00x0.60x0.37, 0.65P**  
CASE 711BG  
ISSUE D

DATE 29 FEB 2024



**GENERIC  
MARKING DIAGRAM\***





XX = Specific Device Code  
M = Date Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G", may or not be present. Some products may not follow the Generic Marking.

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2018.
2. ALL DIMENSION ARE IN MILLIMETERS.
3. DIMENSION  $b$  APPLIES TO THE PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 FROM THE TERMINAL TIP.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.34        | 0.37 | 0.40 |
| A1  | ---         | ---  | 0.05 |
| b   | 0.45        | 0.50 | 0.55 |
| D   | 1.00 BSC    |      |      |
| D1  | ---         | ---  | 0.05 |
| E   | 0.60 BSC    |      |      |
| e   | 0.65 BSC    |      |      |
| L   | 0.22 REF    |      |      |
| L1  | 0.24        | 0.28 | 0.34 |



RECOMMENDED MOUNTING FOOTPRINT\*

\* FOR ADDITIONAL INFORMATION ON OUR Pb-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

|                         |                                      |                                                                                                                                                                                  |
|-------------------------|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON15241G</b>                   | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>X2DFNW2 1.00x0.60x0.37, 0.65P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)