NTHD3100C

MOSFET – Power, Complementary, ChipFET

20 V, +3.9 A /-4.4 A

ON Semiconductor®

http://onsemi.com

$V_{(BR)DSS}$	$R_{DS(on)}$ Typ	I_D MAX
N–Channel 20 V	58 mΩ @ 4.5 V	3.9 A
	77 mΩ @ 2.5 V	
P–Channel –20 V	64 mΩ @ –4.5 V	–4.4 A
	85 mΩ @ –2.5 V	

Features

- Complementary N–Channel and P–Channel MOSFET
- Small Size, 40% Smaller than TSOP–6 Package
- Leadless SMD Package Provides Great Thermal Characteristics
- Trench P–Channel for Low On Resistance
- Low Gate Charge N–Channel for Test Switching
- Pb–Free Packages are Available

Applications

- DC–DC Conversion Circuits
- Load Switch Applications Requiring Level Shift
- Drive Small Brushless DC Motors
- Ideal for Power Management Applications in Portable, Battery Powered Products



N–Channel MOSFET P–Channel MOSFET



ChipFET
CASE 1206A
STYLE 2

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter			Symbol	Value	Unit
Drain–to–Source Voltage			V_{DSS}	20	V
Gate–to–Source Voltage	N–Ch		V_{GS}	±12	V
	P–Ch			±8.0	
N–Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	2.9	A
		T_A = 85°C		2.1	
	t ≤ 10 s	T_A = 25°C		3.9	
P–Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	–3.2	A
		T_A = 85°C		–2.3	
	t ≤ 10 s	T_A = 25°C		–4.4	
Power Dissipation (Note 1)	Steady State	T_A = 25°C	P_D	1.1	W
	t ≤ 5 s			3.1	
Pulsed Drain Current (Note 1)	N–Ch	t = 10 μs	I_{DM}	12	A
	P–Ch	t = 10 μs		–13	
Operating Junction and Storage Temperature			T_J, T_{STG}	–55 to 150	°C
Source Current (Body Diode)			I_S	2.5	A
Lead Temperature for Soldering Purposes (1/8″ from case for 10 seconds)			T_L	260	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Surface–mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces).

PIN CONNECTIONS



MARKING DIAGRAM



C9 = Specific Device Code
M = Month Code
▪ = Pb–Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

© Semiconductor Components Industries, LLC, 2006

May, 2019 – Rev. 3

Publication Order Number:
NTHD3100C/D

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction−to−Ambient − Steady State (Note 2)	$R_{\theta JA}$	113	°C/W
Junction−to−Ambient − t ≤ 10 s (Note 2)	$R_{\theta JA}$	60	°C/W

2. Surface−mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 in sq [1 oz] including traces).

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	N/P	Test Conditions		Min	Typ	Max	Unit
OFF CHARACTERISTICS (Note 3)								
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	N	V_{GS} = 0 V	I_D = 250 μA	20			V
		P		I_D = −250 μA	−20			
Zero Gate Voltage Drain Current	I_{DSS}	N	V_{GS} = 0 V, V_{DS} = 16 V	T_J = 25 °C			1.0	μA
		P	V_{GS} = 0 V, V_{DS} = −16 V				−1.0	
		N	V_{GS} = 0 V, V_{DS} = 16 V	T_J = 125 °C			5.0	
		P	V_{GS} = 0 V, V_{DS} = −16 V				−5.0	
Gate−to−Source Leakage Current	I_{GSS}	N	V_{DS} = 0 V, V_{GS} = ±12 V				±100	nA
		P	V_{DS} = 0 V, V_{GS} = ±8.0 V				±100	
ON CHARACTERISTICS (Note 3)								
Gate Threshold Voltage	$V_{GS(TH)}$	N	V_{GS} = V_{DS}	I_D = 250 μA	0.6		1.2	V
		P		I_D = −250 μA	−.45		−1.5	
Drain−to−Source On Resistance	$R_{DS(on)}$	N	V_{GS} = 4.5 V , I_D = 2.9 A			58	80	mΩ
		P	V_{GS} = −4.5 V , I_D = −3.2 A			64	80	
		N	V_{GS} = 2.5 V , I_D = 2.3 A			77	115	
		P	V_{GS} = −2.5 V, I_D = −2.2 A			85	110	
Forward Transconductance	g_{FS}	N	V_{DS} = 10 V, I_D = 2.9 A			6.0		S
		P	V_{DS} = −10 V , I_D = −3.2 A			8.0		
CHARGES AND CAPACITANCES								
Input Capacitance	C_{ISS}	N	f = 1 MHz, V_{GS} = 0 V	V_{DS} = 10 V		165		pF
		P		V_{DS} = −10 V		680		
Output Capacitance	C_{OSS}	N		V_{DS} = 10 V		80		
		P		V_{DS} = −10 V		100		
Reverse Transfer Capacitance	C_{RSS}	N		V_{DS} = 10 V		25		
		P		V_{DS} = −10 V		70		
Total Gate Charge	$Q_{G(TOT)}$	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 2.9 A			2.3		nC
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −3.2 A			7.4		
Threshold Gate Charge	$Q_{G(TH)}$	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 2.9 A			0.2		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −3.2 A			0.6		
Gate−to−Source Gate Charge	Q_{GS}	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 2.9 A			0.4		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −3.2 A			1.4		
Gate−to−Drain “Miller” Charge	Q_{GD}	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 2.9 A			0.7		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −3.2 A			2.5		

3. Pulse Test: pulse width ≤ 250 μs, duty cycle ≤ 2%.

ELECTRICAL CHARACTERISTICS (continued) (T_J = 25°C unless otherwise noted)

Parameter	Symbol	N/P	Test Conditions		Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS (Note 4)								
Turn−On Delay Time	$t_{d(ON)}$	N	V_{GS} = 4.5 V, V_{DD} = 10 V, I_D = 2.9 A, R_G = 2.5 Ω			6.3		ns
Rise Time	t_r					10.7		
Turn−Off Delay Time	$t_{d(OFF)}$					9.6		
Fall Time	t_f					1.5		
Turn−On Delay Time	$t_{d(ON)}$	P	V_{GS} = −4.5 V, V_{DD} = −10 V, I_D = −3.2 A, R_G = 2.5 Ω			5.8		
Rise Time	t_r					11.7		
Turn−Off Delay Time	$t_{d(OFF)}$					16		
Fall Time	t_f					12.4		
DRAIN−SOURCE DIODE CHARACTERISTICS								
Forward Diode Voltage	V_{SD}	N	V_{GS} = 0 V, T_J = 25 °C	I_S = 2.5 A		0.8	1.15	V
		P		I_S = −2.5 A		−0.8	−1.2	
Reverse Recovery Time	t_{RR}	N	V_{GS} = 0 V, dI_S / dt = 100 A/μs	I_S = 1.5 A		12.5		ns
		P		I_S = −1.5 A		13.5		
Charge Time	t_a	N		I_S = 1.5 A		9.0		
		P		I_S = −1.5 A		9.5		
Discharge Time	t_b	N		I_S = 1.5 A		3.5		
		P		I_S = −1.5 A		4.0		
Reverse Recovery Charge	Q_{RR}	N		I_S = 1.5 A		6.0		nC
		P		I_S = −1.5 A		6.5		

4. Switching characteristics are independent of operating junction temperatures.

TYPICAL N−CHANNEL PERFORMANCE CURVES

(T_J = 25°C unless otherwise noted)



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate−to−Source Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL N−CHANNEL PERFORMANCE CURVES

(T_J = 25°C unless otherwise noted)



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 9. Resistive Switching Time Variation vs. Gate Resistance



Figure 10. Diode Forward Voltage vs. Current

TYPICAL P−CHANNEL PERFORMANCE CURVES

(T_J = 25°C unless otherwise noted)



Figure 11. On−Region Characteristics



Figure 12. Transfer Characteristics



Figure 13. On−Resistance vs. Gate−to−Source Voltage



Figure 14. On−Resistance vs. Drain Current and Gate Voltage



Figure 15. On−Resistance Variation with Temperature



Figure 16. Drain−to−Source Leakage Current vs. Voltage

TYPICAL P−CHANNEL PERFORMANCE CURVES

(T_J = 25°C unless otherwise noted)



Figure 17. Capacitance Variation



Figure 18. Gate−to−Source and Drain−to−Source Voltage vs. Total Charge



Figure 19. Resistive Switching Time Variation vs. Gate Resistance



Figure 20. Diode Forward Voltage vs. Current

DEVICE ORDERING INFORMATION

Device	Package	Shipping†
NTHD3100CT1	ChipFET	3000 / Tape & Reel
NTHD3100CT1G	ChipFET (Pb−Free)	3000 / Tape & Reel
NTHD3100CT3	ChipFET	10000 / Tape & Reel
NTHD3100CT3G	ChipFET (Pb−Free)	10000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

ChipFET is a trademark of Vishay Siliconix.



SCALE 1:1

ChipFET™
CASE1206A−03
ISSUE K

DATE 19 MAY 2009



RESET

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MOLD GATE BURRS SHALL NOT EXCEED 0.13 MM PER SIDE.
4. LEADFRAME TO MOLDED BODY OFFSET IN HORIZONTAL AND VERTICAL SHALL NOT EXCEED 0.08 MM.
5. DIMENSIONS A AND B EXCLUSIVE OF MOLD GATE BURRS.
6. NO MOLD FLASH ALLOWED ON THE TOP AND BOTTOM LEAD SURFACE.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	1.00	1.05	1.10	0.039	0.041	0.043
b	0.25	0.30	0.35	0.010	0.012	0.014
c	0.10	0.15	0.20	0.004	0.006	0.008
D	2.95	3.05	3.10	0.116	0.120	0.122
E	1.55	1.65	1.70	0.061	0.065	0.067
e	0.65 BSC			0.025 BSC		
e1	0.55 BSC			0.022 BSC		
L	0.28	0.35	0.42	0.011	0.014	0.017
H_E	1.80	1.90	2.00	0.071	0.075	0.079
θ	5° NOM			5° NOM		

STYLE 1:
PIN 1. DRAIN
2. DRAIN
3. DRAIN
4. GATE
5. SOURCE
6. DRAIN
7. DRAIN
8. DRAIN

STYLE 2:
PIN 1. SOURCE 1
2. GATE 1
3. SOURCE 2
4. GATE 2
5. DRAIN 2
6. DRAIN 2
7. DRAIN 1
8. DRAIN 1

STYLE 3:
PIN 1. ANODE
2. ANODE
3. SOURCE
4. GATE
5. DRAIN
6. DRAIN
7. CATHODE
8. CATHODE

STYLE 4:
PIN 1. COLLECTOR
2. COLLECTOR
3. COLLECTOR
4. BASE
5. EMITTER
6. COLLECTOR
7. COLLECTOR
8. COLLECTOR

STYLE 5:
PIN 1. ANODE
2. ANODE
3. DRAIN
4. DRAIN
5. SOURCE
6. GATE
7. CATHODE
8. CATHODE

STYLE 6:
PIN 1. ANODE
2. DRAIN
3. DRAIN
4. GATE
5. SOURCE
6. DRAIN
7. DRAIN
8. CATHODE / DRAIN

SOLDERING FOOTPRINT



Basic Style

GENERIC MARKING DIAGRAM*

XXX = Specific Device Code
M = Month Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

OPTIONAL SOLDERING FOOTPRINTS ON PAGE 2

DOCUMENT NUMBER:	**98AON03078D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**ChipFET**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

ChipFET™
CASE 1206A−03
ISSUE K

DATE 19 MAY 2009

ADDITIONAL SOLDERING FOOTPRINTS*



Styles 1 and 4



Style 2



Style 3



Style 5

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON03078D**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**ChipFET**	**PAGE 2 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales