

# Trench-based Schottky Diode, 200 mA, 30 V

## NSR02301MX4

These Trench Schottky diodes are optimized for low forward voltage drop and low leakage current that offers the most optimal power dissipation in applications. They are housed in space saving micro-packaging ideal for space constrained applications.

### Features

- Small Body Outline Dimensions
  - ◆ 01005 Size: 0.445 mm x 0.24 mm
- 200 mA Continuous Forward Current
- Low Forward Voltage Drop – 350 mV (Typical) @  $I_F = 100$  mA
- Low Reverse Current – 25  $\mu$ A (Typical) @  $V_R = 30$  V
- Very Low  $t_{rr}$  – 11 ns Maximum
- Low Capacitance – 19 pF Typical

### Typical Applications

- Mobile and Wearable Devices
- Camera Photo Flash
- Buck and Boost DC–DC Converters
- Reverse Voltage and Current Protection
- Clamping & Protection

### MAXIMUM RATINGS


| Rating                                                                    | Symbol    | Value | Unit |
|---------------------------------------------------------------------------|-----------|-------|------|
| Forward Current (DC)                                                      | $I_F$     | 200   | mA   |
| Reverse Voltage                                                           | $V_R$     | 30    | V    |
| Repetitive Peak Forward Current<br>(Pulse Wave = 1 sec, Duty Cycle = 66%) | $I_{FRM}$ | 1.0   | A    |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



**ON Semiconductor®**

[www.onsemi.com](http://www.onsemi.com)



### MARKING DIAGRAM



X4DFN2  
CASE 718AA



E = Specific Device Code

M = Date Code

### ORDERING INFORMATION

| Device         | Package             | Shipping†              |
|----------------|---------------------|------------------------|
| NSR02301MX4T5G | X4DFN2<br>(Pb-Free) | 10000 /<br>Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# THERMAL CHARACTERISTICS

| Characteristic                                                                                           | Symbol                   | Max          | Unit                     |
|----------------------------------------------------------------------------------------------------------|--------------------------|--------------|--------------------------|
| Thermal Resistance<br>Junction-to-Ambient (Note 1)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$ | $R_{\theta JA}$<br>$P_D$ | 614.9<br>203 | $^\circ\text{C/W}$<br>mW |
| Thermal Resistance<br>Junction-to-Ambient (Note 2)<br>Total Power Dissipation @ $T_A = 25^\circ\text{C}$ | $R_{\theta JA}$<br>$P_D$ | 239.4<br>522 | $^\circ\text{C/W}$<br>mW |
| Junction Temperature Range                                                                               | $T_J$                    | -55 to +125  | $^\circ\text{C}$         |
| Storage Temperature Range                                                                                | $T_{STG}$                | -55 to +150  | $^\circ\text{C}$         |
| Lead Solder Temperature - Maximum (10 seconds)                                                           | $T_L$                    | 260          | $^\circ\text{C}$         |

1. Mounted onto a 4 in<sup>2</sup> FR-4 board 10 mm<sup>2</sup> 1 oz. Cu 0.06" thick single-sided. Operating to steady state.
2. Mounted onto a 4 in<sup>2</sup> FR-4 board 2 cm<sup>2</sup> 1 oz. Cu 0.06" thick single-sided. Operating to steady state.




Figure 1. Thermal Response (Note 1)




Figure 2. Thermal Response (Note 2)

# NSR02301MX4

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic                                                                                        | Symbol          | Min | Typ               | Max               | Unit |
|-------------------------------------------------------------------------------------------------------|-----------------|-----|-------------------|-------------------|------|
| Reverse Leakage<br>(V <sub>R</sub> = 10 V)<br>(V <sub>R</sub> = 30 V)                                 | I <sub>R</sub>  |     | 15<br>25          | 50<br>100         | μA   |
| Forward Voltage<br>(I <sub>F</sub> = 50 mA)<br>(I <sub>F</sub> = 100 mA)<br>(I <sub>F</sub> = 200 mA) | V <sub>F</sub>  |     | 300<br>350<br>420 | 440<br>480<br>540 | mV   |
| Total Capacitance<br>(V <sub>R</sub> = 5.0 V, f = 1 MHz)                                              | C <sub>T</sub>  |     | 19                |                   | pF   |
| Reverse Recovery Time<br>(I <sub>F</sub> = I <sub>R</sub> = 10 mA, I <sub>R(REC)</sub> = 1.0 mA)      | t <sub>rr</sub> |     | 9.4               | 11                | ns   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## TYPICAL CHARACTERISTICS




Figure 3. Forward Voltage




Figure 4. Leakage Current






Figure 5. Total Capacitance



**X4DFN2, 0.44x0.24x0.18, 0.27P**  
**CASE 718AA**  
**ISSUE B**


DATE 05 MAR 2025



**NOTES:**

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. EXPOSED COPPER ALLOWED AS SHOWN.

| MILLIMETERS |           |       |       |
|-------------|-----------|-------|-------|
| DIM         | MIN       | NOM   | MAX   |
| A           | 0.150     | 0.180 | 0.210 |
| A1          | ---       | ---   | 0.030 |
| b           | 0.170     | 0.185 | 0.200 |
| D           | 0.415     | 0.445 | 0.475 |
| E           | 0.210     | 0.240 | 0.270 |
| e           | 0.270 BSC |       |       |
| k           | 0.125     | ---   | ---   |
| L           | 0.105     | 0.120 | 0.135 |



**RECOMMENDED MOUNTING FOOTPRINT**

- \* For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**GENERIC  
MARKING DIAGRAMS\***



X = Specific Device Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

|                         |                                      |                                                                                                                                                                                  |
|-------------------------|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON29067G</b>                   | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>X4DFN2, 0.44x0.24x0.18, 0.27P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)