BQ27Z561-R1 Impedance Track™ Battery Gas Gauge Solution for 1-Series Cell Li-Ion Battery Packs

1 Features

- Supports high-side and low-side current sense resistors down to 1 mΩ
- Supports pack-side gauging including enhanced state of health (SOH) algorithm
- Fast QMAX update option based on predicted OCV
- SHA-256 authentication responder for increased battery pack security
- Sophisticated charge algorithms:
  - JEITA
  - Enhanced charging
  - *RSOC()* charging compensation option
- Two independent ADCs
  - Support for simultaneous current and voltage sampling
  - High-accuracy coulomb counter with input offset error < 1 µV (typical)
- Low-voltage (2-V) operation
- Wide-range current applications (1 mA to > 5 A)
- Active high or low pulse or level interrupt pin
- Supports battery trip point (BTP)
- Reduced power modes (typical battery pack operating range conditions)
  - Typical SLEEP mode: < 11 µA
  - Typical DEEP SLEEP mode: < 9 µA
  - Typical OFF mode: < 1.9 µA
- Internal and external temperature sense functions
- Diagnostic lifetime data monitor and black box recorder
- 400-kHz I²C bus communications interface for high-speed programming and data access
- HDQ one-wire for communication with host
- Compact 12-pin DSBGA package (YPH)

2 Applications

- Smartphones
- Digital still cameras and video cameras
- Tablet computing
- Portable and wearable health devices
- Portable audio devices

3 Description

The Texas Instruments BQ27Z561-R1 Impedance Track™ gas gauge solution is a highly integrated, accurate 1-series cell gas gauge with a flash programmable custom reduced instruction-set CPU (RISC) and SHA-256 authentication for li-ion and li-polymer battery packs. The 1-series cell capability includes parallel cells for increased capacity.

The BQ27Z561-R1 gas gauge communicates via I²C-compatible and HDQ one-wire interfaces and includes several key features that can help facilitate accurate gas gauging applications. Integrated temperature sense functions (internal and external options) enable system and battery temperature measurements.

Device Information

PART NUMBER(1)	PACKAGE	BODY SIZE (NOM)
BQ27Z561-R1	DSBGA (12)	1.67 mm × 2.05 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.



Simplified Schematic

An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. PRODUCTION DATA.

Table of Contents

1 Features....1
2 Applications....1
3 Description....1
4 Revision History....2
5 Description (cont.)....3
6 Pin Configuration and Functions....3
7 Specifications....4
7.1 Absolute Maximum Ratings....4
7.2 ESD Ratings....4
7.3 Recommended Operating Conditions....4
7.4 Thermal Information....5
7.5 Supply Current....5
7.6 Internal 1.8-V LDO (REG18)....5
7.7 I/O (PULS, INT)....5
7.8 Chip Enable (CE)....5
7.9 Internal Temperature Sensor....6
7.10 NTC Thermistor Measurement Support....6
7.11 Coulomb Counter (CC)....6
7.12 Analog Digital Converter (ADC)....6
7.13 Internal Oscillator Specifications....7
7.14 Voltage Reference1 (REF1)....7
7.15 Voltage Reference2 (REF2)....7
7.16 Flash Memory....7
7.17 I^{2}C I/O....7
7.18 I^{2}C Timing — 100 kHz....8
7.19 I^{2}C Timing — 400 kHz....8
7.20 HDQ Timing....8
7.21 Typical Characteristics....10
8 Detailed Description....11
8.1 Overview....11
8.2 Functional Block Diagram....11
8.3 Feature Description....11
8.4 Device Functional Modes....13
9 Applications and Implementation....14
9.1 Application Information....15
9.2 Typical Applications....15
10 Power Supply Requirements....17
11 Layout....18
11.1 Layout Guidelines....18
11.2 Layout Example....19
12 Device and Documentation Support....20
12.1 Documentation Support....20
12.2 Receiving Notification of Documentation Updates....20
12.3 Support Resources....20
12.4 Trademarks....20
12.5 Electrostatic Discharge Caution....20
12.6 Glossary....20
13 Mechanical, Packaging, Orderable Information....20

4 Revision History

Changes from Revision A (August 2019) to Revision B (December 2022) **Page**

- Changed the *Simplified Schematic* 1
- Removed the CE reference from I/O section....5
- Added Chip Enable (CE), which includes CE pin thresholds that are assured by design....5

Changes from Revision * (March 2019) to Revision A (August 2019) **Page**

- Changed body size in *Device Information* 1

Copyright © 2022 Texas Instruments Incorporated

5 Description (cont.)

The integrated SHA-256 functionality helps enable secure identification between systems and packs. The interrupt and BTP functions facilitate the BQ27Z561-R1 device to inform the system when a specific state-of-charge (SOC), voltage, or temperature condition occurs. The low-voltage operation enables the system to continue monitoring the battery even in deeply discharged conditions. During low-activity situations, the device can be set to the low power coulomb counting (CC) mode, which enables the device to continue its coulomb counting while reducing operating current significantly.

6 Pin Configuration and Functions



Table 6-1. Pin Functions

NUMBER	NAME	I/O	DESCRIPTION
D2	BAT	P(1)	Battery voltage measurement input. Kelvin battery sense connection to BAT_SNS. Connect a capacitor (1 µF) between BAT and VSS. Place the capacitor close to the gauge.
D3	CE	I	Active high chip enable
C2	BAT_SNS	AI	Battery sense
A1	INT	O	Interrupt for voltage, temperature, and state of charge (programmable active high or low)
A2	PULS	O	Programmable pulse width with active high or low option
B1	TS	AI	Temperature input for ADC
C3	NU	NU	Makes no external connection
B3	SCL	I/O	Serial clock for I^2C interface; requires external pull up when used. It can be left floating if unused.
A3	SDA/HDQ	I/O	Serial data for I^2C interface and one-wire interface for HDQ (selectable); requires external pull up when used. It can be left floating if unused.
D1	SRP	I	Analog input pin connected to the internal coulomb counter peripheral for integrating a small voltage between SRP (positive side) and SRN
C1	SRN	I	Analog input pin connected to the internal coulomb counter peripheral for integrating a small voltage between SRP (positive side) and SRN.
B2	VSS	P	Device ground

(1) P = Power Connection, O = Digital Output, AI = Analog Input, I = Digital Input, I/O = Digital Input/Output, NU = Not Used

Copyright © 2022 Texas Instruments Incorporated

7 Specifications

7.1 Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
Input Voltage	BAT	–0.3	6	V
	INT, PULS, CE	–0.3	6	V
	SRP, SRN, BAT_SNS	–0.3	V_{BAT} + 0.3	V
	TS	–0.3	2.1	V
	SCL, SDA/HDQ	–0.3	6	V
Operating ambient temperature, T_A		–40	85	°C
Operating junction temperature, T_J		–40	125	°C
Storage temperature, T_{stg}		–65	150	°C

(1) Operation outside the Absolute Maximum Ratings may cause permanent device damage. Absolute Maximum Ratings do not imply functional operation of the device at these or any other conditions beyond those listed under Recommended Operating Conditions. If outside the Recommended Operating Conditions but within the Absolute Maximum Ratings, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.

7.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human-body model (HBM) on all pins, per ANSI/ESDA/JEDEC JS-001(1)	±1500	V
		Charged-device model (CDM) on all pins, per JEDEC specification JESD22-C101(2)	±500	

(1) JEDEC document JEP155 states that 500-V HBM enables safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM enables safe manufacturing with a standard ESD control process.

7.3 Recommended Operating Conditions

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

			MIN	NOM	MAX	UNIT
V_{BAT}	Supply voltage	No operating restrictions	2.0		5.5	V
C_{BAT}	External capacitor from BAT to VSS		1			µF
V_{TS}	Temperature sense		0		1.8	V
V_{PULS}, V_{INT}, V_{CE}	Input and output pins		0		V_{BAT}	V
V_{SCL}, $V_{SDA/HDQ}$	Communication pins		0		V_{BAT}	V

Copyright © 2022 Texas Instruments Incorporated

7.4 Thermal Information

Over-operating free-air temperature range (unless otherwise noted)

THERMAL METRIC[1]		BQ27Z561-R1 DSBGA (YPH) (12 PINS)	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	64.1	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	59.8	
$R_{\theta JB}$	Junction-to-board thermal resistance	52.7	
ψ_{JT}	Junction-to-top characterization parameter	0.3	
ψ_{JB}	Junction-to-board characterization parameter	28.3	
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	2.4	

(1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report (SPRA953).

7.5 Supply Current

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
I_{NORMAL}	Standard operating Conditions		60		µA
I_{SLEEP}	Sense resistor current below SLEEP mode threshold		11		µA
$I_{DEEPSLEEP}$	Sense resistor current below DEEP SLEEP mode threshold		9		µA
I_{OFF}	CE = V_{IL}		0.5		µA

7.6 Internal 1.8-V LDO (REG18)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{REG18}	Regulator output voltage		1.6	1.8	2.0	V
V_{PORth}	POR threshold	Rising Threshold	1.45		1.7	V
V_{PORhy}	POR hysteresis			0.1		V

7.7 I/O (PULS, INT)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IH}	High-level input voltage	V_{REG18} = 1.8 V	1.15			V
V_{IL}	Low-level input voltage low	V_{REG18} = 1.8 V			0.50	V
V_{OL}	Output voltage low	V_{REG18} = 1.8 V, I_{OL} = 1 mA			0.4	V
C_I	Input capacitance			5		pF
I_{lkg}	Input leakage current				1	µA

7.8 Chip Enable (CE)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IH}	High-level input voltage[1]		0.75 × V_{BAT}			V
V_{IL}	Low-level input voltage low[1]				0.25 × V_{BAT}	V

(1) Assured by design

Copyright © 2022 Texas Instruments Incorporated

7.9 Internal Temperature Sensor

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(TEMP)}$	Internal Temperature sensor voltage drift	V_{TEMPP}	1.65	1.73	1.8	mV/°C
		$V_{TEMPP} – V_{TEMPN}$ (assured by design)	0.17	0.18	0.19	

7.10 NTC Thermistor Measurement Support

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$R_{NTRC(PU)}$	Internal pullup resistance		14.4	18	21.6	kΩ
$R_{NTC(DRIFT)}$	Resistance drift over temperature		–250	–120	0	PPM/°C

7.11 Coulomb Counter (CC)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(CC_IN)}$	Differential input voltage range		–0.1		0.1	V
$t_{(CC_CONV)}$	Conversion time	Single conversion		1000		ms
	Effective Resolution	1 LSB		3.8		µV
	Integral nonlinearity	16-bit, Best fit over input voltage range	–22.3	5.2	+22.3	LSB
	Differential nonlinearity	16-bit, No missing codes		1.5		LSB
	Offset error	16- bit Post-Calibration	–2.6	1.3	+2.6	LSB
	Offset error drift	15-bit + sign, Post Calibration		0.04	0.07	LSB/°C
	Gain Error	15-bit + sign, Over input voltage range	–492	131	+492	LSB
	Gain Error drift	15-bit + sign, Over input voltage range		4.3	9.8	LSB/°C
	Effective input resistance		7			MΩ

7.12 Analog Digital Converter (ADC)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{ADC_TS_GPIO}$	Input voltage range	$V_{FS} = V_{REF2}$	–0.2		1.0	V
		$V_{FS} = V_{REG18} * 2$	–0.2		1.44	V
V_{BAT_MODE}	Battery Input Voltage		–0.2		5.5	V
	Integral nonlinearity	16-bit, Best fit, –0.1 V to 0.8 * V_{REF2}	–8.4		+8.4	LSB
	Differential nonlinearity	16-bit, No missing codes		1.5		LSB
	Offset error	16-bit Post-Calibration(1), $V_{FS} = V_{REF2}$	–4.2	1.8	+4.2	LSB
	Offset error drift	16-bit Post-Calibration(1), $V_{FS} = V_{REF2}$		0.02	0.1	LSB/°C
	Gain Error	16-bit, –0.1 to 0.8 * V_{FS}	–492	131	+492	LSB
	Gain Error drift	16-bit, –0.1 to 0.8 * V_{FS}		2	4.5	LSB/°C
	Effective input resistance		8			MΩ
$t_{(ADC_CONV)}$	Conversion time			11.7		ms
Effective resolution			14	15		bits

(1) Factory calibration.

Copyright © 2022 Texas Instruments Incorporated

7.13 Internal Oscillator Specifications

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
High Frequency Oscillator (HFO)						
f_{HFO}	Operating frequency			16.78		MHz
f_{HFO}	HFO frequency drift	TA = –20°C to 70°C	–2.5%		2.5%	
		TA = –40°C to 85°C	–3.5		3.5	
$t_{HFOSTART}$	HFO start-up time	T_A = –40°C to 85°C, oscillator frequency within +/– 3% of nominal frequency or a power-on reset			4	ms
Low Frequency Oscillator (LFO)						
f_{LFO}	Operating frequency			65.536		kHz
$f_{LFO(ERR)}$	Frequency error	T_A = –40°C to 85°C	–2.5%		+2.5%	

7.14 Voltage Reference1 (REF1)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{REF1}	Internal reference voltage(1)		1.195	1.21	1.227	V
V_{REF1_DRIFT}	Internal reference voltage drift	T_A = –40 °C to 85°C	–80		+80	PPM/C

(1) Used for CC and LDO

7.15 Voltage Reference2 (REF2)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{REF2}	Internal reference voltage(1)		1.2	1.21	1.22	V
V_{REF2_DRIFT}	Internal reference voltage drift	T_A = –40 °C to 85°C	–20		20	PPM/°C

(1) Used for ADC

7.16 Flash Memory

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
	Data retention		10	100		Years
	Flash programming write cycles	Data Flash	20000			Cycles
		Instruction Flash	1000			Cycles
$t_{(ROWPROG)}$	Row programming time				40	µs
$t_{(MASSERASE)}$	Mass-erase time	TA = –40°C to 85°C			40	ms
$t_{(PAGEERASE)}$	Page-erase time	TA = –40°C to 85°C			40	ms
$I_{FLASHREAD}$	Flash read current	TA = –40°C to 85°C			1	mA
$I_{FLASHWRTIE}$	Flash write current	TA = –40°C to 85°C			5	mA
$I_{FLASHERASE}$	Flash erase current	TA = –40°C to 85°C			15	mA

7.17 I²C I/O

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IH}	High-level input voltage	SCL, SDA/HDQ, V_{REG18} = 1.8 V	1.26			V
V_{IL}	Low-level input voltage low	V_{REG18} = 1.8 V			0.54	V
V_{OL}	Low-level output voltage	I_{OL} = 1 mA, V_{REG18} = 1.8 V			0.36	V

Copyright © 2022 Texas Instruments Incorporated

7.17 I²C I/O (continued)

Unless otherwise noted, characteristics noted under conditions of T_A = –40°C to 85°C

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
C_I	Input capacitance				10	pF
I_{lkg}	Input leakage current			1		µA

7.18 I²C Timing — 100 kHz

PARAMETER		TEST CONDITIONS	MIN	NOM	MAX	UNIT
f_{SCL}	Clock operating frequency	SCL duty cycle = 50%			100	kHz
$t_{HD:STA}$	Start condition hold time		4.0			µs
t_{LOW}	Low period of the SCL Clock		4.7			µs
t_{HIGH}	High period of the SCL Clock		4.0			µs
$t_{SU:STA}$	Setup repeated START		4.7			µs
$t_{HD:DAT}$	Data hold time (SDA input)		0			ns
$t_{SU:DAT}$	Data setup time (SDA input)		250			ns
t_r	Clock rise time	10% to 90%			1000	ns
t_f	Clock fall time	90% to 10%			300	ns
$t_{SU:STO}$	Setup time STOP condition		4.0			µs
t_{BUF}	Bus free time STOP to START		4.7			µs

7.19 I²C Timing — 400 kHz

PARAMETER		TEST CONDITIONS	MIN	NOM	MAX	UNIT
f_{SCL}	Clock operating frequency	SCL duty cycle = 50%			400	kHz
$t_{HD:STA}$	START condition hold time		0.6			µs
t_{LOW}	Low period of the SCL Clock		1.3			µs
t_{HIGH}	High period of the SCL Clock		600			ns
$t_{SU:STA}$	Setup repeated START		600			ns
$t_{HD:DAT}$	Data hold time (SDA input)		0			ns
$t_{SU:DAT}$	Data setup time (SDA input)		100			ns
t_r	Clock rise time	10% to 90%			300	ns
t_f	Clock fall time	90% to 10%			300	ns
$t_{SU:STO}$	Setup time STOP condition		0.6			µs
t_{BUF}	Bus free time STOP to START		1.3			µs

7.20 HDQ Timing

PARAMETER		TEST CONDITIONS	MIN	NOM	MAX	UNIT
t_B	Break time		190			µs
t_{BR}	Break recovery time		40			µs
t_{HW1}	Host write 1 time	Host drives HDQ	0.5		50	µs
t_{HW0}	Host write 0 time	Host drives HDQ	86		145	µs
t_{CYCH}	Cycle time, host to device	Device drives HDQ	190			µs
t_{CYCD}	Cycle time, device to Host	Device drives HDQ	190	205	250	µs
t_{DW1}	Device write 1 time	Device drives HDQ	32		50	µs
t_{DW0}	Device write 0 time	Device drives HDQ	80		145	µs
t_{RSPS}	Device response time	Device drives HDQ	190		950	µs

Copyright © 2022 Texas Instruments Incorporated

7.20 HDQ Timing (continued)

PARAMETER		TEST CONDITIONS	MIN	NOM	MAX	UNIT
t_{TRND}	Host turn around time	Host drives HDQ after device drives HDQ	250			µs
t_{RISE}	HDQ line rising time to logic 1				1.8	µs
t_{RST}	HDQ Reset	Host drives HDQ low before device reset	2.2			s



Figure 7-1. I²C Timing



a. HDQ Breaking
b. Rise time of HDQ line
c. HDQ Host to fuel gauge communication
d. Fuel gauge to Host communication
e. Fuel gauge to Host response format
f. HDQ Host to fuel gauge

Figure 7-2. HDQ Timing

Copyright © 2022 Texas Instruments Incorporated

7.21 Typical Characteristics



A. BAT Min = 2 V BAT Nom = 3.6 V BAT Max = 5 V

Figure 7-3. REF1 Voltage Versus Battery and Temperature



A. BAT Min = 2 V BAT Nom = 3.6 V BAT Max = 5 V

Figure 7-4. LDO Voltage Versus Battery and Temperature



A. BAT Min = 2 V BAT Nom = 3.6 V BAT Max = 5 V

Figure 7-5. LFO Frequency Versus Battery and Temperature



A. BAT Min = 2 V BAT Nom = 3.6 V BAT Max = 5 V

Figure 7-6. ADVC Offset Voltage Versus Battery and Temperature

Copyright © 2022 Texas Instruments Incorporated

8 Detailed Description

8.1 Overview

The BQ27Z561-R1 gas gauge is a fully integrated battery manager that employs flash-based firmware to provide a complete solution for battery-stack architectures composed of 1-series cells. The BQ27Z561-R1 device interfaces with a host system via an I^2C or HDQ protocol. High-performance, integrated analog peripherals enable support for a sense resistor down to 1 mΩ, and simultaneous current/voltage data conversion for instant power calculations. The following sections detail all of the major component blocks included as part of the BQ27Z561-R1 device.

8.2 Functional Block Diagram



Copyright © 2017, Texas Instruments Incorporated

8.3 Feature Description

8.3.1 BQ27Z561-R1 Processor

The BQ27Z561-R1 device uses a custom TI-proprietary processor design that features a Harvard architecture and operates at frequencies up to 4.2 MHz. Using an adaptive, three-stage instruction pipeline, the BQ27Z561-R1 processor supports variable instruction lengths of 8, 16, or 24 bits.

8.3.2 Battery Parameter Measurements

The BQ27Z561-R1 device measures cell voltage and current simultaneously, and also measures temperature to calculate the information related to remaining capacity, full charge capacity, state-of-health, and other gauging parameters.

8.3.2.1 Coulomb Counter (CC)

The first ADC is an integrating analog-to-digital converter designed specifically for tracking charge and discharge activity, or coulomb counting, of a rechargeable battery. It features a single-channel differential input that converts the voltage difference across a sense resistor between the SRP and SRN terminals with a resolution of 3.74 µV.

8.3.2.2 CC Digital Filter

The CC digital filter generates a 16-bit conversion value from the delta-sigma CC front-end. Its FIR filter uses the HFO clock output. New conversions are available every 1 s.

8.3.2.3 ADC Multiplexer

The ADC multiplexer provides selectable connections to the external pins BAT, BAT_SNS, TS, the internal temperature sensor, internal reference voltages, internal 1.8-V regulator, and VSS ground reference input. In addition, the multiplexer can independently enable the TS input connection to the internal thermistor biasing circuitry, and enables the user to short the multiplexer inputs for test and calibration purposes.

8.3.2.4 Analog-to-Digital Converter (ADC)

The second ADC is a 16-bit delta-sigma converter designed for general-purpose measurements. The ADC automatically scales the input voltage range during sampling based on channel selection. The converter resolution is a function of its full-scale range and number of bits, yielding a 38-µV resolution.

8.3.2.5 Internal Temperature Sensor

An internal temperature sensor is available on the BQ27Z561-R1 device to reduce the cost, power, and size of the external components necessary to measure temperature. It is available for connection to the ADC using the multiplexer, and is ideal for quickly determining pack temperature under a variety of operating conditions.

8.3.2.6 External Temperature Sensor Support

The TS input is enabled with an internal 18-kΩ (Typ.) linearization pull-up resistor to support the use of a 10-kΩ (25°C) NTC external thermistor, such as the Semitec 103AT-2. The NTC thermistor should be connected between VSS and the individual TS pin. The analog measurement is then taken via the ADC through its input multiplexer. If a different thermistor type is required, then changes to configurations may be required.



Figure 8-1. External Thermistor Biasing

Copyright © 2022 Texas Instruments Incorporated

8.3.3 Power Supply Control

The BQ27Z561-R1 device uses the BAT pin as its power source. BAT powers the internal voltage sources that supply references for the device. BAT_SNS is a non-current carrying path and used at the Kelvin reference for BAT.

8.3.4 Bus Communication Interface

The BQ27Z561-R1 device has an I^2C bus communication interface. Alternatively, the BQ27Z561-R1 can be configured to communicate through the HDQ pin (shared with SDA).

Note

Once the device is switched to the HDQ protocol, it is not reversible.

8.3.5 Low Frequency Oscillator

The BQ27Z561-R1 device includes a low frequency oscillator (LFO) running at 65.536 kHz.

8.3.6 High Frequency Oscillator

The BQ27Z561-R1 includes a high frequency oscillator (HFO) running at 16.78 MHz. It is frequency locked to the LFO output and scaled down to 8.388 MHz with a 50% duty cycle.

8.3.7 1.8-V Low Dropout Regulator

The BQ27Z561-R1 device contains an integrated capacitor-less 1.8-V LDO (REG18) that provides regulated supply voltage for the device CPU and internal digital logic.

8.3.8 Internal Voltage References

The BQ27Z561-R1 device provides two internal voltage references. REF1 is used by REG18, oscillators, and CC. REF2 is used by the ADC.

8.3.9 Gas Gauging

This device uses the Impedance Track™ technology to measure and determine the available charge in battery cells. See the *Theory and Implementation of Impedance Track Battery Fuel-Gauging Algorithm Application Report* (SLUA450) for further details.

8.3.10 Charge Control Features

This device supports charge control features, such as:

- Reports charging voltage and charging current based on the active temperature range—JEITA temperature ranges T1, T2, T3, T4, T5, and T6
- Provides more complex charging profiles, including sub-ranges within a standard temperature range
- Reports the appropriate charging current required for constant current charging, and the appropriate charging voltage needed for constant voltage charging to a smart charger, using the bus communication interface
- Compensates the charging profile based on the value of *RelativeStateOfCharge()*
- Selects the chemical state-of-charge of each battery cell using the Impedance Track method
- Reports charging faults and indicates charge status via charge and discharge alarms

8.3.11 Authentication

This device supports security with the following features, which can be enabled if desired:

- Authentication by the host using the SHA-256 method
- The gas gauge requires SHA-256 authentication before the device can be unsealed or allow full access.

8.4 Device Functional Modes

This device supports four modes, but the current consumption varies, based on firmware control of certain functions and modes of operation:

Copyright © 2022 Texas Instruments Incorporated

- NORMAL mode: In this mode, the device performs measurements, calculations, protections, and data updates every 250-ms intervals. Between these intervals, the device is operating in a reduced power stage to minimize total average current consumption.
- SLEEP mode: In this mode, the device performs measurements, calculations, and data updates in adjustable time intervals. Between these intervals, the device is operating in a reduced power stage to minimize total average current consumption.
- DEEP SLEEP mode: In this mode, the current is reduced slightly while current and voltage are still measured periodically, with a user-defined time between reads.
- OFF mode: The device is completely disabled by pulling CE low. CE disables the internal voltage rail. All non-volatile memory is unprotected.

8.4.1 Lifetime Logging Features

The device supports data logging of several key parameters for warranty and analysis:

- Maximum and minimum cell temperature
- Maximum current in CHARGE or DISCHARGE mode
- Maximum and minimum cell voltages
- Total run time (This data is stored with a resolution of two hours.)
- Time spent different temperature ranges (This data is stored with a resolution of two hours.)

8.4.2 Configuration

The device supports accurate data measurements and data logging of several key parameters.

8.4.2.1 Coulomb Counting

The device uses an integrating delta-sigma analog-to-digital converter (ADC) for current measurement. The ADC measures charge/discharge flow of the battery by measuring the voltage across a very small external sense resistor. The integrating ADC measures a bipolar signal from a range of –100 mV to 100 mV, with a positive value when $V_{(SRP)} – V_{(SRN)}$, indicating charge current and a negative value indicating discharge current.

The current measurement is performed by measuring the voltage drop across the external sense resistor, which can be as low as 1 mΩ, and the polarity of the differential voltage determines if the cell is in the CHARGE or DISCHARGE mode.

8.4.2.2 Cell Voltage Measurements

The BQ27Z561-R1 gas gauge measures the cell voltage at 1-s intervals using the ADC. This measured value is internally scaled for the ADC and is calibrated to reduce any errors due to offsets. This data is also used for calculating the impedance of the cell for Impedance Track gas gauging.

8.4.2.3 Auto Calibration

The auto-calibration feature helps to cancel any voltage offset across the SRP and SRN pins for accurate measurement of the cell voltage, charge/discharge current, and thermistor temperature. The auto-calibration is performed when there is no communication activity for a minimum of 5 s on the bus lines.

8.4.2.4 Temperature Measurements

This device has an internal sensor for on-die temperature measurements, and the ability to support an external temperature measurement via the external NTC on the TS pin. These two measurements are individually enabled and configured.

9 Applications and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Copyright © 2022 Texas Instruments Incorporated

9.1 Application Information

The BQ27Z561-R1 gas gauge can be used with a 1-series li-ion/li-polymer battery pack. To implement and design a comprehensive set of parameters for a specific battery pack, the user needs Battery Management Studio (BQSTUDIO), which is a graphical user-interface tool installed on a PC during development. The firmware installed in the product has default values, which are summarized in the *BQ27Z561-R1 Technical Reference Manual* (SLUUBY5). Using the BQSTUDIO tool, these default values can be changed to cater to specific application requirements during development once the system parameters, such as enable/disable of certain features for operation, cell configuration, chemistry that best matches the cell used, and more are known. The final flash image, which is extracted once configuration and testing are complete, will be used for mass production and is referred to as the "golden image."

9.2 Typical Applications

The following is an example BQ27Z561-R1 application schematic for a single-cell battery pack.



Figure 9-1. BQ27Z561-R1 Typical Implementation with Low-side Current Sensing



Figure 9-2. BQ27Z561-R1 Typical Implementation with High-side Current Sensing

9.2.1 Design Requirements (Default)

Table 9-1. Default Design Requirements

Design Parameter	Example
Cell Configuration	1s1p (1 series with 1 parallel)
Design Capacity	5300 mAh
Device Chemistry	li-ion
Design Voltage	4000 mV
Cell Low Voltage	2500 mV

9.2.2 Detailed Design Procedure

9.2.2.1 Changing Design Parameters

For the firmware settings needed for the design requirements, refer to the *BQ27Z561-R1 Technical Reference Manual* (SLUUBY5).

- To change design capacity, set the data flash value (in mAh) in the ***Gas Gauging: Design: Design Capacity*** register.
- To set device chemistry, go to the data flash ***I²C Configuration: Data: Device Chemistry***. The BQSTUDIO software automatically populates the correct chemistry identification. This selection is derived from using the BQCHEM feature in the tools and choosing the option that matches the device chemistry from the list.
- To set the design voltage, go to ***Gas Gauging: Design: Design Voltage*** register.
- To set the Cell ***Low Voltage*** or clear the Cell ***Low Voltage***, use ***Settings: Configuration: Init Voltage Low Set*** or ***Clear***. This is used to set the cell voltage level that will set (clear) the *[VOLT_LO]* bit in the *Interrupt Status* register.

Copyright © 2022 Texas Instruments Incorporated

- To enable the internal temperature and the external temperature sensors: Set ***Settings:Configuration: Temperature Enable***: Bit 0 (TSInt) = 1 for the internal sensor; set Bit 1 (TS1) = 1 for the external sensor.

9.2.3 Calibration Process

The calibration of current, voltage, and temperature readings is accessible by writing 0xF081 or 0xF082 to *ManufacturerAccess()*. A detailed procedure is included in the *BQ27Z561-R1 Technical Reference Manual* (SLUUBY5) in the *Calibration* section. The description allows for calibration of cell voltage measurement offset, battery voltage, current calibration, coulomb counter offset, PCB offset, CC gain/capacity gain, and temperature measurement for both internal and external sensors.

9.2.4 Gauging Data Updates

When a battery pack enabled with the BQ27Z561-R1 gas gauge is cycled, the value of *FullChargeCapacity()* updates several times, including the onset of charge or discharge, charge termination, temperature delta, resistance updates during discharge, and relaxation. Figure 9-3 shows actual battery voltage, load current, and *FullChargeCapacity()* when some of those updates occur during a single application cycle.

Update points from the plot include:

- Charge termination at 7900 s
- Relaxation at 9900 s
- Resistance update at 11500 s

9.2.4.1 Application Curve



Figure 9-3. Full Charge Capacity Tracking (X-Axis Is Seconds)

10 Power Supply Requirements

The only power supply is the BAT pin, which is connected to the positive terminal of the battery. The input voltage for the BAT pin will have a minimum of 2 V to a maximum of 5 V.

Copyright © 2022 Texas Instruments Incorporated

11 Layout

11.1 Layout Guidelines

- The quality of the Kelvin connections at the sense resistor is critical. The sense resistor must have a temperature coefficient no greater than 50 ppm to minimize current measurement drift with temperature. Choose the value of the sense resistor to correspond to the available overcurrent and short-circuit ranges of the BQ27Z561-R1 gas gauge. Select the smallest value possible to minimize the negative voltage generated on the BQ27Z561-R1 VSS node during a short circuit. This pin has an absolute minimum of –0.3 V. Parallel resistors can be used as long as good Kelvin sensing is ensured. The device is designed to support a 1-mΩ to 3-mΩ sense resistor.
- BAT_SNS should be tied directly to the positive connection of the battery. It should not share a path with the BAT pin.
- In reference to the gas gauge circuit the following features require attention for component placement and layout: differential low-pass filter and I^2C communication.
- The BQ27Z561-R1 gas gauge uses an integrating delta-sigma ADC for current measurements. Add a 100-Ω resistor from the sense resistor to the SRP and SRN inputs of the device. Place a 0.1-µF filter capacitor across the SRP and SRN inputs. If required for a circuit, 0.1-µF filter capacitors can be added for additional noise filtering for each sense input pin to ground. Place all filter components as close as possible to the device. Route the traces from the sense resistor in parallel to the filter circuit. Adding a ground plane around the filter network can provide additional noise immunity.
- The BQ27Z561-R1 has an internal LDO that is internally compensated and does not require an external decoupling capacitor.
- The I^2C clock and data pins have integrated high-voltage ESD protection circuits; however, adding a Zener diode and series resistor provides more robust ESD performance. The I^2C clock and data lines have an internal pull-down. When the gas gauge senses that both lines are low (such as during removal of the pack), the device performs auto-offset calibration and then goes into SLEEP mode to conserve power.

Copyright © 2022 Texas Instruments Incorporated

11.2 Layout Example



Figure 11-1. BQ27Z561-R1 Key Trace Board Layout

12 Device and Documentation Support

12.1 Documentation Support

12.1.1 Related Documentation

- *BQ27Z561-R1 Technical Reference Manual*
- *Theory and Implementation of Impedance Track Battery Fuel-Gauging Algorithm Application Report*

12.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

12.3 Support Resources

TI E2E™ support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

12.4 Trademarks

Impedance Track™ and TI E2E™ are trademarks of Texas Instruments.
All trademarks are the property of their respective owners.

12.5 Electrostatic Discharge Caution

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12.6 Glossary

TI Glossary	This glossary lists and explains terms, acronyms, and definitions.

13 Mechanical, Packaging, Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2022 Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
BQ27Z561YPHR-R1	Active	Production	DSBGA (YPH) | 12	3000 | LARGE T&R	Yes	SAC396	Level-1-260C-UNLIM	-40 to 85	Q27Z561R1
BQ27Z561YPHR-R1.A	Active	Production	DSBGA (YPH) | 12	3000 | LARGE T&R	Yes	SAC396	Level-1-260C-UNLIM	-40 to 85	Q27Z561R1
BQ27Z561YPHR-R1.B	Active	Production	DSBGA (YPH) | 12	3000 | LARGE T&R	Yes	SAC396	Level-1-260C-UNLIM	-40 to 85	Q27Z561R1

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
BQ27Z561YPHR-R1	DSBGA	YPH	12	3000	180.0	8.4	1.83	2.2	0.53	4.0	8.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
BQ27Z561YPHR-R1	DSBGA	YPH	12	3000	182.0	182.0	20.0

PACKAGE OUTLINE

YPH0012

DSBGA - 0.4 mm max height

DIE SIZE BALL GRID ARRAY



D: Max = 2.08 mm, Min = 2.02 mm

E: Max = 1.705 mm, Min =1.644 mm

4222640/A 12/2015

NanoFree Is a trademark of Texas Instruments.

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. NanoFree™ package configuration.



LAND PATTERN EXAMPLE
SCALE:30X



SOLDER MASK DETAILS
NOT TO SCALE

4222640/A 12/2015

NOTES: (continued)

4. Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints.
For more information, see Texas Instruments literature number SNVA009 (www.ti.com/lit/snva009).

EXAMPLE STENCIL DESIGN

YPH0012

DSBGA - 0.4 mm max height

DIE SIZE BALL GRID ARRAY



SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:40X

4222640/A 12/2015

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2025, Texas Instruments Incorporated