

# SN54ALS157A, SN54ALS158 SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158 QUADRUPLE 1-OF-2 DATA SELECTORS/MULTIPLEXERS

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994


- Buffered Inputs and Outputs
- Package Options Include Plastic Small-Outline (D) Packages, Ceramic Chip Carriers (FK), and Standard Plastic (N) and Ceramic (J) 300-mil DIPs

## description


These data selectors/multiplexers contain inverters and drivers to supply full data selection to the four output gates. A separate strobe ( $\overline{G}$ ) input is provided. A 4-bit word is selected from one of two sources and is routed to the four outputs. The 'ALS157A and SN74AS157 present true data. The 'ALS158 and SN74AS158 present inverted data to minimize propagation delay time.

The SN54ALS157A and SN54ALS158 are characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The SN74ALS157A, SN74ALS158, SN74AS157, and SN74AS158 are characterized for operation from  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ .

SN54ALS157A, SN54ALS158 . . . J PACKAGE  
SN74ALS157A, SN74ALS158,  
SN74AS157, SN74AS158 . . . D OR N PACKAGE  
(TOP VIEW)



SN54ALS157A, SN54ALS158 . . . FK PACKAGE  
(TOP VIEW)



NC – No internal connection


FUNCTION TABLE

| INPUTS         |                  |      |   | OUTPUT Y              |                      |
|----------------|------------------|------|---|-----------------------|----------------------|
| $\overline{G}$ | $\overline{A/B}$ | DATA |   | 'ALS157A<br>SN74AS157 | 'ALS158<br>SN74AS158 |
|                |                  | A    | B |                       |                      |
| H              | X                | X    | X | L                     | H                    |
| L              | L                | L    | X | L                     | H                    |
| L              | L                | H    | X | H                     | L                    |
| L              | H                | X    | L | L                     | H                    |
| L              | H                | X    | H | H                     | L                    |

# **SN54ALS157A, SN54ALS158** **SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158** **QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS**

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

## **logic symbols†**







† These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.  
Pin numbers shown are for the D, J, and N packages.

**SN54ALS157A, SN54ALS158**  
**SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158**  
**QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS**

SDAS081C - APRIL 1982 - REVISED DECEMBER 1994

**logic diagrams (positive logic)**



Pin numbers shown are for the D, J, and N packages.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265  
 POST OFFICE BOX 1443 • HOUSTON, TEXAS 77251-1443

# SN54ALS157A, SN54ALS158 SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158 QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|                                                                       |                |
|-----------------------------------------------------------------------|----------------|
| Supply voltage, $V_{CC}$                                              | 7 V            |
| Input voltage, $V_I$                                                  | 7 V            |
| Operating free-air temperature range, $T_A$ : SN54ALS157A, SN54ALS158 | –55°C to 125°C |
| SN74ALS157A, SN74ALS158                                               | 0°C to 70°C    |
| Storage temperature range                                             | –65°C to 150°C |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

## recommended operating conditions

|          |                                | SN54ALS157A<br>SN54ALS158 |     |      | SN74ALS157A<br>SN74ALS158 |     |      | UNIT |
|----------|--------------------------------|---------------------------|-----|------|---------------------------|-----|------|------|
|          |                                | MIN                       | NOM | MAX  | MIN                       | NOM | MAX  |      |
| $V_{CC}$ | Supply voltage                 | 4.5                       | 5   | 5.5  | 4.5                       | 5   | 5.5  | V    |
| $V_{IH}$ | High-level input voltage       | 2                         |     |      | 2                         |     |      | V    |
| $V_{IL}$ | Low-level input voltage        |                           |     | 0.7  |                           |     | 0.8  | V    |
| $I_{OH}$ | High-level output current      |                           |     | –0.4 |                           |     | –0.4 | mA   |
| $I_{OL}$ | Low-level output current       |                           |     | 4    |                           |     | 8    | mA   |
| $T_A$    | Operating free-air temperature | –55                       |     | 125  | 0                         |     | 70   | °C   |

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER  | TEST CONDITIONS                                                      | SN54ALS157A<br>SN54ALS158               |                  |      | SN74ALS157A<br>SN74ALS158 |                  |      | UNIT |
|------------|----------------------------------------------------------------------|-----------------------------------------|------------------|------|---------------------------|------------------|------|------|
|            |                                                                      | MIN                                     | TYP <sup>‡</sup> | MAX  | MIN                       | TYP <sup>‡</sup> | MAX  |      |
| $V_{IK}$   | $V_{CC} = 4.5\text{ V}$ , $I_I = -18\text{ mA}$                      |                                         |                  | –1.2 |                           |                  | –1.2 | V    |
| $V_{OH}$   | $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ , $I_{OH} = -0.4\text{ mA}$ | $V_{CC} - 2$                            |                  |      | $V_{CC} - 2$              |                  |      | V    |
| $V_{OL}$   | $V_{CC} = 4.5\text{ V}$                                              | $I_{OL} = 4\text{ mA}$                  |                  | 0.25 | 0.4                       | 0.25             |      | 0.4  |
|            |                                                                      | $I_{OL} = 8\text{ mA}$                  |                  |      |                           | 0.35             |      | 0.5  |
| $I_I$      | $V_{CC} = 5.5\text{ V}$ , $V_I = 7\text{ V}$                         |                                         |                  | 0.1  |                           |                  | 0.1  | mA   |
| $I_{IH}$   | $V_{CC} = 5.5\text{ V}$ , $V_I = 2.7\text{ V}$                       |                                         |                  | 20   |                           |                  | 20   | μA   |
| $I_{IL}$   | $V_{CC} = 5.5\text{ V}$ , $V_I = 0.4\text{ V}$                       |                                         |                  | –0.1 |                           |                  | –0.1 | mA   |
| $I_O^{\S}$ | $V_{CC} = 5.5\text{ V}$ , $V_O = 2.25\text{ V}$                      | –20                                     |                  | –112 | –30                       |                  | –112 | mA   |
| $I_{CC}$   | 'ALS157A                                                             | $V_{CC} = 5.5\text{ V}$ ,<br>See Note 1 |                  | 6    | 11                        | 6                |      | 11   |
|            | 'ALS158                                                              |                                         |                  | 5    | 10                        | 5                |      | 10   |

<sup>‡</sup> All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

<sup>\S</sup> The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

NOTE 1:  $I_{CC}$  is measured with 4.5 V applied to all inputs and all outputs open.

**SN54ALS157A, SN54ALS158**  
**SN74ALS157A, SN74ALS158, SN74ALS157, SN74ALS158**  
**QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS**

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

switching characteristics (see Figure 1)

| PARAMETER        | FROM<br>(INPUT)  | TO<br>(OUTPUT) | V <sub>CC</sub> = 5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = 25°C | V <sub>CC</sub> = 4.5 V to 5.5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = MIN to MAX† |     |             |     | UNIT |
|------------------|------------------|----------------|-------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----|-------------|-----|------|
|                  |                  |                | 'ALS157A                                                                                              | SN54ALS157A                                                                                                             |     | SN74ALS157A |     |      |
|                  |                  |                | TYP                                                                                                   | MIN                                                                                                                     | MAX | MIN         | MAX |      |
| t <sub>PLH</sub> | A or B           | Y              | 9                                                                                                     | 4                                                                                                                       | 17  | 4           | 14  | ns   |
| t <sub>PHL</sub> |                  |                | 6                                                                                                     | 2                                                                                                                       | 15  | 2           | 12  |      |
| t <sub>PLH</sub> | $\overline{A}/B$ | Y              | 15                                                                                                    | 7                                                                                                                       | 28  | 7           | 24  | ns   |
| t <sub>PHL</sub> |                  |                | 9                                                                                                     | 4                                                                                                                       | 20  | 4           | 17  |      |
| t <sub>PLH</sub> | $\overline{G}$   | Y              | 14                                                                                                    | 7                                                                                                                       | 25  | 7           | 20  | ns   |
| t <sub>PHL</sub> |                  |                | 10                                                                                                    | 4                                                                                                                       | 18  | 4           | 13  |      |

<sup>†</sup> For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

switching characteristics (see Figure 1)

| PARAMETER        | FROM<br>(INPUT) | TO<br>(OUTPUT) | V <sub>CC</sub> = 5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = 25°C | V <sub>CC</sub> = 4.5 V to 5.5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = MIN to MAX† |     |            |     | UNIT |
|------------------|-----------------|----------------|-------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----|------------|-----|------|
|                  |                 |                | 'ALS158                                                                                               | SN54ALS158                                                                                                              |     | SN74ALS158 |     |      |
|                  |                 |                | TYP                                                                                                   | MIN                                                                                                                     | MAX | MIN        | MAX |      |
| t <sub>PLH</sub> | A or B          | Y              | 9                                                                                                     | 4                                                                                                                       | 18  | 4          | 15  | ns   |
| t <sub>PHL</sub> |                 |                | 5                                                                                                     | 2                                                                                                                       | 12  | 2          | 8   |      |
| t <sub>PLH</sub> | A̅/B            | Y              | 13                                                                                                    | 5                                                                                                                       | 22  | 5          | 18  | ns   |
| t <sub>PHL</sub> |                 |                | 13                                                                                                    | 5                                                                                                                       | 22  | 5          | 18  |      |
| t <sub>PLH</sub> | G̅              | Y              | 13                                                                                                    | 5                                                                                                                       | 22  | 5          | 18  | ns   |
| t <sub>PHL</sub> |                 |                | 13                                                                                                    | 5                                                                                                                       | 22  | 5          | 18  |      |

<sup>†</sup> For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.



# SN54ALS157A, SN54ALS158 SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158 QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

## absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>

|                                                                    |                |
|--------------------------------------------------------------------|----------------|
| Supply voltage, $V_{CC}$                                           | 7 V            |
| Input voltage, $V_I$                                               | 7 V            |
| Operating free-air temperature range, $T_A$ : SN74AS157, SN74AS158 | 0°C to 70°C    |
| Storage temperature range                                          | –65°C to 150°C |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

## recommended operating conditions

|          |                                | SN74AS157<br>SN74AS158 |     |     | UNIT |
|----------|--------------------------------|------------------------|-----|-----|------|
|          |                                | MIN                    | NOM | MAX |      |
| $V_{CC}$ | Supply voltage                 | 4.5                    | 5   | 5.5 | V    |
| $V_{IH}$ | High-level input voltage       | 2                      |     |     | V    |
| $V_{IL}$ | Low-level input voltage        |                        |     | 0.8 | V    |
| $I_{OH}$ | High-level output current      |                        |     | –2  | mA   |
| $I_{OL}$ | Low-level output current       |                        |     | 20  | mA   |
| $T_A$    | Operating free-air temperature | 0                      |     | 70  | °C   |

## electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER    |                    | TEST CONDITIONS                                                    | SN74AS157<br>SN74AS158 |                  |      | UNIT          |
|--------------|--------------------|--------------------------------------------------------------------|------------------------|------------------|------|---------------|
|              |                    |                                                                    | MIN                    | TYP <sup>‡</sup> | MAX  |               |
| $V_{IK}$     |                    | $V_{CC} = 4.5\text{ V}$ , $I_I = -18\text{ mA}$                    |                        |                  | –1.2 | V             |
| $V_{OH}$     |                    | $V_{CC} = 4.5\text{ V to } 5.5\text{ V}$ , $I_{OH} = -2\text{ mA}$ | $V_{CC} - 2$           |                  |      | V             |
| $V_{OL}$     |                    | $V_{CC} = 4.5\text{ V}$ , $I_{OL} = 20\text{ mA}$                  |                        | 0.35             | 0.5  | V             |
| $I_I$        | $\bar{A}/B$        | $V_{CC} = 5.5\text{ V}$ , $V_I = 7\text{ V}$                       |                        |                  | 0.2  | mA            |
|              | A, B, or $\bar{G}$ |                                                                    |                        |                  | 0.1  |               |
| $I_{IH}$     | $\bar{A}/B$        | $V_{CC} = 5.5\text{ V}$ , $V_I = 2.7\text{ V}$                     |                        |                  | 40   | $\mu\text{A}$ |
|              | A, B, or $\bar{G}$ |                                                                    |                        |                  | 20   |               |
| $I_{IL}$     | $\bar{A}/B$        | $V_{CC} = 5.5\text{ V}$ , $V_I = 0.4\text{ V}$                     |                        |                  | –1   | mA            |
|              | A, B, or $\bar{G}$ |                                                                    |                        |                  | –0.5 |               |
| $I_{O}^{\S}$ |                    | $V_{CC} = 5.5\text{ V}$ , $V_O = 2.25\text{ V}$                    | –30                    |                  | –112 | mA            |
| $I_{CC}$     | SN74AS157          | $V_{CC} = 5.5\text{ V}$                                            |                        | 17.5             | 28   | mA            |
|              | SN74AS158          |                                                                    |                        | 15.6             | 22.5 |               |

<sup>‡</sup> All typical values are at  $V_{CC} = 5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

<sup>\S</sup> The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current,  $I_{OS}$ .

**SN54ALS157A, SN54ALS158**  
**SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158**  
**QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS**

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

**switching characteristics (see Figure 1)**

| PARAMETER        | FROM<br>(INPUT)  | TO<br>(OUTPUT) | V <sub>CC</sub> = 4.5 V to 5.5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = MIN to MAX† |      | UNIT |
|------------------|------------------|----------------|-------------------------------------------------------------------------------------------------------------------------|------|------|
|                  |                  |                | SN74AS157                                                                                                               |      |      |
|                  |                  |                | MIN                                                                                                                     | MAX  |      |
| t <sub>PLH</sub> | A or B           | Y              | 1                                                                                                                       | 6    | ns   |
| t <sub>PHL</sub> |                  |                | 1                                                                                                                       | 5.5  |      |
| t <sub>PLH</sub> | $\overline{A}/B$ | Y              | 2                                                                                                                       | 11   | ns   |
| t <sub>PHL</sub> |                  |                | 2                                                                                                                       | 10   |      |
| t <sub>PLH</sub> | $\overline{G}$   | Y              | 2                                                                                                                       | 10.5 | ns   |
| t <sub>PHL</sub> |                  |                | 2                                                                                                                       | 7.5  |      |

† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.

**switching characteristics (see Figure 1)**

| PARAMETER        | FROM<br>(INPUT)  | TO<br>(OUTPUT) | V <sub>CC</sub> = 4.5 V to 5.5 V,<br>C <sub>L</sub> = 50 pF,<br>R <sub>L</sub> = 500 Ω,<br>T <sub>A</sub> = MIN to MAX† |      | UNIT |
|------------------|------------------|----------------|-------------------------------------------------------------------------------------------------------------------------|------|------|
|                  |                  |                | SN74AS158                                                                                                               |      |      |
|                  |                  |                | MIN                                                                                                                     | MAX  |      |
| t <sub>PLH</sub> | A or B           | Y              | 1                                                                                                                       | 5    | ns   |
| t <sub>PHL</sub> |                  |                | 1                                                                                                                       | 4.5  |      |
| t <sub>PLH</sub> | $\overline{A}/B$ | Y              | 2                                                                                                                       | 9.5  | ns   |
| t <sub>PHL</sub> |                  |                | 2                                                                                                                       | 10.5 |      |
| t <sub>PLH</sub> | $\overline{G}$   | Y              | 2                                                                                                                       | 6.5  | ns   |
| t <sub>PHL</sub> |                  |                | 2                                                                                                                       | 10   |      |


† For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions.



# SN54ALS157A, SN54ALS158 SN74ALS157A, SN74ALS158, SN74AS157, SN74AS158 QUAD 1-OF-2 DATA SELECTORS/MULTIPLEXERS

SDAS081C – APRIL 1982 – REVISED DECEMBER 1994

## PARAMETER MEASUREMENT INFORMATION SERIES 54ALS/74ALS AND 54AS/74AS DEVICES



- NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.  
C. When measuring propagation delay items of 3-state outputs, switch S1 is open.  
D. All input pulses have the following characteristics: PRR  $\leq$  1 MHz,  $t_r = t_f = 2$  ns, duty cycle = 50%.  
E. The outputs are measured one at a time with one transition per measurement.

Figure 1. Load Circuits and Voltage Waveforms

## PACKAGING INFORMATION

| Orderable part number          | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                      |
|--------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|------------------------------------------|
| <a href="#">5962-86869012A</a> | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-<br>86869012A<br>SNJ54ALS<br>157AFK |
| <a href="#">5962-8686901EA</a> | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8686901EA<br>SNJ54ALS157AJ          |
| <a href="#">5962-8862501EA</a> | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8862501EA<br>SNJ54ALS158J           |
| <a href="#">SN54ALS157AJ</a>   | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54ALS157AJ                             |
| SN54ALS157AJ.A                 | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | SN54ALS157AJ                             |
| <a href="#">SN74ALS157AD</a>   | Obsolete      | Production           | SOIC (D)   16  | -                     | -           | Call TI                              | Call TI                           | 0 to 70      | ALS157A                                  |
| <a href="#">SN74ALS157ADR</a>  | Active        | Production           | SOIC (D)   16  | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS157A                                  |
| SN74ALS157ADR.A                | Active        | Production           | SOIC (D)   16  | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS157A                                  |
| <a href="#">SN74ALS157AN</a>   | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74ALS157AN                             |
| SN74ALS157AN.A                 | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74ALS157AN                             |
| <a href="#">SN74ALS157ANSR</a> | Active        | Production           | SOP (NS)   16  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS157A                                  |
| SN74ALS157ANSR.A               | Active        | Production           | SOP (NS)   16  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS157A                                  |
| <a href="#">SN74ALS158D</a>    | Active        | Production           | SOIC (D)   16  | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS158                                   |
| SN74ALS158D.A                  | Active        | Production           | SOIC (D)   16  | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS158                                   |
| <a href="#">SN74ALS158N</a>    | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74ALS158N                              |
| SN74ALS158N.A                  | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74ALS158N                              |
| <a href="#">SN74ALS158NSR</a>  | Active        | Production           | SOP (NS)   16  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS158                                   |
| SN74ALS158NSR.A                | Active        | Production           | SOP (NS)   16  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | ALS158                                   |
| <a href="#">SN74AS157D</a>     | Active        | Production           | SOIC (D)   16  | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AS157                                    |
| SN74AS157D.A                   | Active        | Production           | SOIC (D)   16  | 40   TUBE             | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | 0 to 70      | AS157                                    |
| <a href="#">SN74AS157N</a>     | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74AS157N                               |
| SN74AS157N.A                   | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74AS157N                               |
| <a href="#">SN74AS158N</a>     | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74AS158N                               |
| SN74AS158N.A                   | Active        | Production           | PDIP (N)   16  | 25   TUBE             | Yes         | NIPDAU                               | N/A for Pkg Type                  | 0 to 70      | SN74AS158N                               |

| Orderable part number          | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6)                  |
|--------------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|--------------------------------------|
| <a href="#">SNJ54ALS157AFK</a> | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-86869012A<br>SNJ54ALS<br>157AFK |
| SNJ54ALS157AFK.A               | Active        | Production           | LCCC (FK)   20 | 55   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-86869012A<br>SNJ54ALS<br>157AFK |
| <a href="#">SNJ54ALS157AJ</a>  | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8686901EA<br>SNJ54ALS157AJ      |
| SNJ54ALS157AJ.A                | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8686901EA<br>SNJ54ALS157AJ      |
| <a href="#">SNJ54ALS158J</a>   | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8862501EA<br>SNJ54ALS158J       |
| SNJ54ALS158J.A                 | Active        | Production           | CDIP (J)   16  | 25   TUBE             | No          | SNPB                                 | N/A for Pkg Type                  | -55 to 125   | 5962-8862501EA<br>SNJ54ALS158J       |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**OTHER QUALIFIED VERSIONS OF SN54ALS157A, SN54ALS158, SN74ALS157A, SN74ALS158 :**

- Catalog : [SN74ALS157A](#), [SN74ALS158](#)
- Military : [SN54ALS157A](#), [SN54ALS158](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Military - QML certified for Military and Defense Applications


## TAPE AND REEL INFORMATION



\*All dimensions are nominal


| Device         | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74ALS157ADR  | SOIC         | D               | 16   | 2500 | 330.0              | 16.4               | 6.5     | 10.3    | 2.1     | 8.0     | 16.0   | Q1            |
| SN74ALS157ANSR | SOP          | NS              | 16   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| SN74ALS158NSR  | SOP          | NS              | 16   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device         | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|----------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74ALS157ADR  | SOIC         | D               | 16   | 2500 | 353.0       | 353.0      | 32.0        |
| SN74ALS157ANSR | SOP          | NS              | 16   | 2000 | 356.0       | 356.0      | 35.0        |
| SN74ALS158NSR  | SOP          | NS              | 16   | 2000 | 356.0       | 356.0      | 35.0        |

**TUBE**


\*All dimensions are nominal

| Device           | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|------------------|--------------|--------------|------|-----|--------|--------|--------|--------|
| 5962-86869012A   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| SN74ALS157AN     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS157AN     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS157AN.A   | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS157AN.A   | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS158D      | D            | SOIC         | 16   | 40  | 507    | 8      | 3940   | 4.32   |
| SN74ALS158D.A    | D            | SOIC         | 16   | 40  | 507    | 8      | 3940   | 4.32   |
| SN74ALS158N      | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS158N      | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS158N.A    | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74ALS158N.A    | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS157D       | D            | SOIC         | 16   | 40  | 507    | 8      | 3940   | 4.32   |
| SN74AS157D.A     | D            | SOIC         | 16   | 40  | 507    | 8      | 3940   | 4.32   |
| SN74AS157N       | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS157N       | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS157N.A     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS157N.A     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS158N       | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS158N       | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS158N.A     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SN74AS158N.A     | N            | PDIP         | 16   | 25  | 506    | 13.97  | 11230  | 4.32   |
| SNJ54ALS157AFK   | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |
| SNJ54ALS157AFK.A | FK           | LCCC         | 20   | 55  | 506.98 | 12.06  | 2030   | NA     |




# PACKAGE OUTLINE

NS0016A

SOP - 2.00 mm max height

SOP




4220735/A 12/2021

## NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm, per side.






4220735/A 12/2021

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

D (R-PDSO-G16)

PLASTIC SMALL OUTLINE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - $\triangle C$  Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
  - $\triangle D$  Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
  - E. Reference JEDEC MS-012 variation AC.

# MECHANICAL DATA

NS (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14-PINS SHOWN



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion, not to exceed 0,15.

## GENERIC PACKAGE VIEW


**FK 20**

**LCCC - 2.03 mm max height**

8.89 x 8.89, 1.27 mm pitch

LEADLESS CERAMIC CHIP CARRIER

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.




4229370VA\


J (R-GDIP-T\*\*)

14 LEADS SHOWN

# CERAMIC DUAL IN-LINE PACKAGE



| PINS **<br>DIM | 14                     | 16                     | 18                     | 20                     |
|----------------|------------------------|------------------------|------------------------|------------------------|
| A              | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC | 0.300<br>(7,62)<br>BSC |
| B MAX          | 0.785<br>(19,94)       | .840<br>(21,34)        | 0.960<br>(24,38)       | 1.060<br>(26,92)       |
| B MIN          | —                      | —                      | —                      | —                      |
| C MAX          | 0.300<br>(7,62)        | 0.300<br>(7,62)        | 0.310<br>(7,87)        | 0.300<br>(7,62)        |
| C MIN          | 0.245<br>(6,22)        | 0.245<br>(6,22)        | 0.220<br>(5,59)        | 0.245<br>(6,22)        |




4040083/F 03/03

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package is hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL STD 1835 GDIP1-T14, GDIP1-T16, GDIP1-T18 and GDIP1-T20.


## N (R-PDIP-T\*\*)

16 PINS SHOWN

## PLASTIC DUAL-IN-LINE PACKAGE



| PINS **             | 14               | 16               | 18               | 20               |
|---------------------|------------------|------------------|------------------|------------------|
| DIM                 |                  |                  |                  |                  |
| A MAX               | 0.775<br>(19,69) | 0.775<br>(19,69) | 0.920<br>(23,37) | 1.060<br>(26,92) |
| A MIN               | 0.745<br>(18,92) | 0.745<br>(18,92) | 0.850<br>(21,59) | 0.940<br>(23,88) |
| MS-001<br>VARIATION | AA               | BB               | AC               | AD               |



14/18 Pin Only  
20 Pin vendor option

4040049/E 12/2002

- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - Falls within JEDEC MS-001, except 18 and 20 pin minimum body length (Dim A).
  - The 20 pin end lead shoulder width is a vendor option, either half or full width.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2025, Texas Instruments Incorporated